



ERIKS Guide ring type Powerslide T100G

Characteristics

Type: Powerslide

Material: T100G

Temperature range: -40 / 100 °C

Internal diameter	Outer diameter	Width	Groove width	Thickness	Article
mm	mm	mm	mm	mm	
20	25	5.5	5.6	2.5	10019605
25	30	9.5	9.7	2.5	10068546
27	32	5.5	5.6	2.5	10019609
30	35	5.5	5.6	2.5	10019610
30	35	9.5	9.7	2.5	10068545
30	35	14.8	15	2.5	10019612
31	36	14.8	15	2.5	10068554
35	40	5.5	5.6	2.5	10019613
35	40	5.5	5.6	2.5	10019698
35	40	9.5	9.7	2.5	10019614
36	41	5.5	5.6	2.5	11014242
40	45	5.5	5.6	2.5	10019615
40	45	9.5	9.7	2.5	10019616
40	45	14.8	15	2.5	10019617
45	50	5.5	5.6	2.5	10019618
45	50	9.5	9.7	2.5	10019619
45	50	14.8	15	2.5	10019620
45	50	24.5	25	2.5	10068549
50	55	5.5	5.6	2.5	10019621
50	55	7.9	8.1	2.5	10019622
50	55	9.5	9.7	2.5	10019623
50	55	14.8	15	2.5	10019624
55	60	5.5	5.6	2.5	10019625
55	60	9.5	9.7	2.5	10019626
55	60	14.8	15	2.5	11166868
58	63	5.5	5.6	2.5	10019627
58	63	9.5	9.7	2.5	10019628
58	63	14.8	15	2.5	10019629
58	63	24.5	25	2.5	10068550
60	65	9.5	9.7	2.5	10019631
60	65	14.8	15	2.5	10019632
65	70	9.5	9.7	2.5	10019635
65	70	9.6	9.5	2.5	11166869
65	70	14.8	15	2.5	10019636
70	75	5.5	5.6	2.5	10019637
70	75	9.5	9.7	2.5	10019638
70	75	14.8	15	2.5	10019639
70	75	24.5	25	2.5	10019640
75	80	5.5	5.6	2.5	10019641
75	80	9.5	9.7	2.5	10019643
75	80	14.8	15	2.5	10019644
75	80	24.5	25	2.5	10068551
80	85	5.5	5.6	2.5	10019646

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Internal diameter	Outer diameter	Width	Groove width	Thickness	Article
mm	mm	mm	mm	mm	
80	85	9.5	9.7	2.5	10019647
80	85	14.8	15	2.5	10019648
85	90	5.5	5.6	2.5	10019650
85	90	9.5	9.7	2.5	10019651
85	90	14.8	15	2.5	10019652
90	95	5.5	5.6	2.5	10019653
90	95	9.5	9.7	2.5	10019654
90	95	14.8	15	2.5	10019655
90	95	19.5	20	2.5	10019656
95	100	5.5	5.6	2.5	10019657
95	100	9.5	9.7	2.5	10019658
95	100	14.8	15	2.5	10019659
95	100	19.5	20	2.5	10068548
95	100	24.5	25	2.5	10019660
100	105	9.5	9.7	2.5	10019662
100	105	14.8	15	2.5	10019663
100	105	24.5	25	2.5	10019664
105	110	9.5	9.7	2.5	10019665
105	110	14.8	15	2.5	10019666
110	115	9.5	9.7	2.5	10019668
110	115	14.8	15	2.5	10019669
115	120	14.8	15	2.5	10019671
115	120	19.5	20	2.5	10019672
120	125	9.5	9.7	2.5	10019673
120	125	14.8	15	2.5	10019674
120	125	24.5	25	2.5	10068552
125	130	9.5	9.7	2.5	10019675
125	130	14.8	15	2.5	10019676
135	140	9.5	9.7	2.5	10019677
135	140	14.8	15	2.5	10019678
135	140	19.5	20	2.5	10019679
135	140	24.5	25	2.5	10019680
145	150	9.5	9.7	2.5	10019681
145	150	14.8	15	2.5	10019682
145	150	19.5	20	2.5	10019683
145	150	24.5	25	2.5	10068553
150	155	14.8	15	2.5	10019685
150	155	24.5	25	2.5	11192297
155	160	14.8	15	2.5	10019686
155	160	19.5	20	2.5	10019687
165	170	14.8	15	2.5	10019688
175	180	14.8	15	2.5	10019689
175	180	19.5	20	2.5	10019690
175	180	24.5	25	2.5	10019691
195	200	14.8	15	2.5	10019692
195	200	19.5	20	2.5	10019693
195	200	24.5	25	2.5	10019694
245	250	14.8	15	2.5	10019696

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.