

ERIFLON Guide strip Eriflon



Characteristics

Type: Geleidestrip Eriflon

Material: ER81

Temperature range: -40 / 225 °C

Width mm	Groove width mm	Thickness mm	Article
2.4	2.6	1.5	10019791
3	3.2	1.5	10019793
3.9	4.1	1.5	10019792
4	4.2	2.5	10019795
5.5	5.7	2.5	10019796
6.1	6.3	2.5	10019797
7.9	8.1	2.5	10019798
8	8.2	1.5	10019775
8	8.2	2	10019776
9.5	9.7	1.5	10019777
9.5	9.7	2.5	10019787
10	10.2	2	10019778
12	12.2	2.5	10019779
14.8	15	2.5	10019788
14.8	15	3	10019814
14.9	15.1	2	10019780
19	19.5	3	10019815
19.5	20	2.5	10019799
19.5	20	3	10019816
20	20.5	2	10019781
24.5	25	2.5	10019789
24.5	25	3	10019817
24.5	25	3	10019783
25	25.5	2	10019782
29.5	30	2.5	10019790
35	35.5	2	10019800
35	35.5	2.5	10019784
40.5	41	2.5	10019786
6.1	6.3	2.5	10019819
9.5	9.7	2.5	10019820
14.8	15	2.5	10019821
19.5	20	2.5	10019822
8	8.2	1.5	10019823
9.5	9.7	2.5	10019824
3	3.2	1.5	10019807
3.9	4.1	1.5	10019806
4	4.2	2.5	10019808
5	5.2	1.5	10019801
5.5	5.7	2.5	10019809
6.1	6.3	2.5	10019810
7.9	8.1	2.5	10019811
9.5	9.7	2.5	10019803
14.8	15	2	10019802

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Width mm	Groove width mm	Thickness mm	Article
14.8	15	2.5	10019804
19.5	20	2.5	10019812
29.5	30	2.5	10019805

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.