



ERIKS Rubber flange gasket EPDM 70 EN 1514-1 IBC

Characteristics

Series: EPDM 70

Compound: 131304

Norm: EN 1514-1 IBC

Hardness (Sh A): 70 Sh A

Colour: Black

Temperature range: -30 / 130 °C

Max. pressure: 10 bar

Suitable for medium: Water, Air [compressed air],
Potable water, Weak Alkalis, Alkalis, Acids, Weak
Acids, Water [process water]

Number of inserts	Nominal diameter	Flange pressure stage	Outer diameter	Inner diameter	Thickness	Flange standard	Article
			mm	mm	mm		
0	DN10	PN10/40	46	18	3	EN 1092-1 RF	12252653
0	DN80	PN10/40	142	89	2	EN 1092-1 RF	11023919
0	DN100	PN10/16	162	115	2	EN 1092-1 RF	11023922
0	DN125	PN10/16	192	141	2	EN 1092-1 RF	11023926
0	DN200	PN10/16	273	220	2	EN 1092-1 RF	11023934
0	DN250	PN10	328	273	3	EN 1092-1 RF	11023950
0	DN300	PN10	378	324	3	EN 1092-1 RF	11023955
0	DN350	PN10	438	356	2	EN 1092-1 RF	11535187
0	DN350	PN10	444	356	3	EN 1092-1 RF	11023986
0	DN400	PN10	489	407	2	EN 1092-1 RF	11535188
0	DN400	PN10	489	407	3	EN 1092-1 RF	11024021
0	DN400	PN25	514	407	3	EN 1092-1 RF	11024023
0	DN500	PN10	594	508	2	EN 1092-1 RF	11535189
0	DN500	PN10	594	508	3	EN 1092-1 RF	11024025
0	DN500	PN16	617	508	3	EN 1092-1 RF	11024028
0	DN500	PN25	624	508	3	EN 1092-1 RF	11024030
0	DN600	PN10	695	610	3	EN 1092-1 RF	11024034
0	DN600	PN25	731	610	3	EN 1092-1 RF	11024039

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.