



ERIKS Rubber flange gasket FKM/FPM 75 EN 1514-1 IBC

Characteristics

Series: FKM/FPM 75

Norm: EN 1514-1 IBC

Hardness (Sh A): 75 Sh A

Colour: Black

Temperature range: -30 / 200 °C

Max. pressure: 10 bar

Suitable for medium: Oil, Fuel oil, Alkalies, Air [compressed air], Water [process water], Grease, Strong acids [except hydrofluoric], Hydrocarbons, Refrigerants, Solvents, Strong Alkalies, Weak Acids, Weak Alkalies, Acids, Biodiesel, Lubricant, Fuels, Water, Strong Acids

Application

- Recommended in: Chemical

Number of inserts	Nominal diameter	Flange pressure stage	Outer diameter	Inner diameter	Thickness	Flange standard	Article
			mm	mm	mm		
0	DN10	PN10/40	46	18	3	EN 1092-1 RF	12252709
0	DN15	PN10/40	51	22	3	EN 1092-1 RF	12252711
0	DN25	PN10/40	71	34	3	EN 1092-1 RF	11159866
0	DN100	PN25/40	168	115	3	EN 1092-1 RF	12252728
0	DN125	PN10/16	192	141	3	EN 1092-1 RF	12252730
0	DN200	PN10/16	273	220	3	EN 1092-1 RF	12252735
0	DN250	PN10	328	273	3	EN 1092-1 RF	12252737
0	DN300	PN10	378	324	3	EN 1092-1 RF	12252740
0	DN350	PN10	438	356	3	EN 1092-1 RF	12252743
0	DN400	PN10	489	407	3	EN 1092-1 RF	12252746
0	DN500	PN10	594	508	3	EN 1092-1 RF	12252749
0	DN600	PN10	695	610	3	EN 1092-1 RF	12252752

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.