



LEADER Fibre flange gasket FYBAR PT50 EN 1514-1 IBC

Characteristics

Series: FYBAR
Type: PT50
Norm: EN 1514-1 IBC
With Inner eyelet: No
Fibre type: Aramid
Anti sticking layer: Yes
Temperature range: -30 / 200 °C
Max. pressure: 85 bar

Characteristics [2]

Suitable for medium: Fuels, Grease, Potable water, Weak Alkalis, Chlorine Water < 5% [7782-50-5], Chlorine, gaseous [7782-50-5], Oil, Weak Acids, Refrigerants, Air [compressed air], Solvents, Biodiesel, Natural gas, Lubricant
Approval according to: BS7531 Grade Y, UBA Elastomerleitlinie, GL, TA-Luft, Blow out VDI2200, DVGW, DVGW W270, HTB DIN30653

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN10	PN10/40	46	18	2	10002931
DN15	PN10/40	51	22	1.5	11915135
DN15	PN10/40	51	22	2	10002932
DN15	PN10/40	51	22	3	11915136
DN20	PN10/40	61	27	1.5	11915137
DN20	PN10/40	61	27	2	10002933
DN20	PN10/40	61	27	3	11915138
DN25	PN10/40	71	34	1.5	11915139
DN25	PN10/40	71	34	2	10002934
DN25	PN10/40	71	34	3	11915140
DN32	PN6	76	43	2	11672111
DN32	PN10/40	82	43	1.5	11915141
DN32	PN10/40	82	43	2	10002935
DN32	PN10/40	82	43	3	11915142
DN40	PN6	86	49	2	11672112
DN40	PN10/40	92	49	1.5	11915143
DN40	PN10/40	92	49	2	10002936
DN40	PN10/40	92	49	3	11915144
DN50	PN6	96	61	2	11672123
DN50	PN10/40	107	61	1.5	11915145
DN50	PN10/40	107	61	2	10002937
DN50	PN10/40	107	61	3	11915146
DN65	PN6	116	77	2	11672124
DN65	PN10/40	127	77	1.5	11915147
DN65	PN10/40	127	77	2	10002938
DN65	PN10/40	127	77	3	11915148
DN80	PN6	132	89	2	11672125
DN80	PN10/40	142	89	1.5	11915149
DN80	PN10/40	142	89	2	10002939
DN80	PN10/40	142	89	3	11883862
DN100	PN10/16	162	115	1.5	11915130
DN100	PN25/40	168	115	1.5	11198756
DN100	PN25/40	168	115	2	11043637
DN100	PN10/16	162	115	2	10002927
DN100	PN6	152	115	2	11672126
DN100	PN10/16	162	115	3	11127461
DN100	PN25/40	168	115	3	11129452
DN125	PN25/40	194	141	1.5	11915179
DN125	PN10/16	192	141	1.5	11915131

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN125	PN10/16	192	141	2	10002928
DN125	PN25/40	194	141	2	11043638
DN125	PN6	182	141	2	11672127
DN125	PN10/16	192	141	3	11115081
DN125	PN25/40	194	141	3	11915180
DN150	PN10/16	218	169	1.5	11258579
DN150	PN25/40	224	169	1.5	11915181
DN150	PN25/40	224	169	2	11043639
DN150	PN10/16	218	169	2	10002929
DN150	PN25/40	224	169	3	11915182
DN150	PN10/16	218	169	3	11915132
DN200	PN10/16	273	220	1.5	11198766
DN200	PN25	284	220	1.5	11915164
DN200	PN40	290	220	1.5	11915183
DN200	PN25	284	220	2	11043650
DN200	PN10/16	273	220	2	10002930
DN200	PN40	290	220	2	11043651
DN200	PN40	290	220	3	11915184
DN200	PN10/16	273	220	3	11012493
DN200	PN25	284	220	3	11915165
DN250	PN40	352	273	1.5	11915185
DN250	PN25	340	273	1.5	11915166
DN250	PN10	328	273	1.5	11198764
DN250	PN16	329	273	1.5	11915150
DN250	PN40	352	273	2	11043654
DN250	PN16	329	273	2	11043652
DN250	PN25	340	273	2	11043653
DN250	PN10	328	273	2	10002921
DN250	PN16	329	273	3	11915151
DN250	PN25	340	273	3	11129493
DN250	PN40	352	273	3	11915186
DN250	PN10	328	273	3	11035226
DN300	PN16	384	324	1.5	11915152
DN300	PN40	417	324	1.5	11915187
DN300	PN25	400	324	1.5	11915167
DN300	PN10	378	324	1.5	11915122
DN300	PN10	378	324	2	10002922
DN300	PN25	400	324	2	11043657
DN300	PN16	384	324	2	11043656
DN300	PN40	417	324	2	11043658
DN300	PN16	384	324	3	11915153
DN300	PN10	378	324	3	11126196
DN300	PN25	400	324	3	11915168
DN300	PN40	417	324	3	11915188
DN350	PN25	457	356	1.5	11915169
DN350	PN40	474	356	1.5	11915189
DN350	PN10	438	356	1.5	11915123
DN350	PN16	444	356	1.5	11915154
DN350	PN10	438	356	2	10002923
DN350	PN16	444	356	2	11043659
DN350	PN40	474	356	2	11043671
DN350	PN25	457	356	2	11043670
DN350	PN40	474	356	3	11915190

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN350	PN25	457	356	3	11915170
DN350	PN10	438	356	3	11883860
DN350	PN16	444	356	3	11915155
DN400	PN40	546	407	1.5	11915191
DN400	PN25	514	407	1.5	11915171
DN400	PN10	489	407	1.5	11915124
DN400	PN16	495	407	1.5	11915156
DN400	PN40	546	407	2	11043674
DN400	PN16	495	407	2	11043672
DN400	PN10	489	407	2	10002924
DN400	PN25	514	407	2	11043673
DN400	PN25	514	407	3	11915172
DN400	PN10	489	407	3	11915125
DN400	PN40	546	407	3	11915192
DN400	PN16	495	407	3	11915157
DN450	PN16	555	458	1.5	11915158
DN450	PN25	564	458	1.5	11915173
DN450	PN40	571	458	1.5	11915193
DN450	PN10	539	458	1.5	11915126
DN450	PN10	539	458	2	11127979
DN450	PN16	555	458	2	12259688
DN450	PN25	564	458	2	12259689
DN450	PN40	571	458	2	12259690
DN450	PN25	564	458	3	11915174
DN450	PN16	555	458	3	11915159
DN450	PN10	539	458	3	11915127
DN450	PN40	571	458	3	11915194
DN500	PN10	594	508	1.5	11915128
DN500	PN16	617	508	1.5	11915160
DN500	PN40	628	508	1.5	11915195
DN500	PN25	624	508	1.5	11915175
DN500	PN40	628	508	2	11043677
DN500	PN25	624	508	2	11043676
DN500	PN10	594	508	2	10002925
DN500	PN16	617	508	2	11043675
DN500	PN10	594	508	3	11012495
DN500	PN25	624	508	3	11915176
DN500	PN40	628	508	3	11915196
DN500	PN16	617	508	3	11915161
DN600	PN25	734	610	1.5	11915177
DN600	PN10	695	610	1.5	11915129
DN600	PN40	747	610	1.5	11915197
DN600	PN16	734	610	1.5	11915162
DN600	PN16	734	610	2	11043679
DN600	PN25	731	610	2	11043680
DN600	PN10	695	610	2	10002926
DN600	PN40	747	610	2	11043681
DN600	PN25	734	610	3	11915178
DN600	PN10	695	610	3	11118668
DN600	PN16	734	610	3	11915163
DN600	PN40	747	610	3	11915198

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.