

ERIKS PTFE flange gasket TEFMET ASME B16.21



Characteristics

Series: TEFMET

Norm: ASME B16.21

Material structure: PTFE, pure, virginal

Marking: Unprinted

Insert material: SS 304 [1.4301]

Temperature range: -100 / 250 °C

Max. pressure: 40 bar

Suitable for medium: Air [compressed air]

Application

- Recommended in: Chemical

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
1/2"	150lbs	48	21	2.5	10001564
1/2"	300/600lbs	54	21	2.5	11913465
3/4"	300/600lbs	67	27	2.5	11913468
3/4"	150lbs	57	27	2.5	10001565
1"	150lbs	67	33	2.5	10001555
1"	300/600lbs	73	33	2.5	11913462
1.1/4"	150lbs	76	42	2.5	10001567
1.1/4"	300/600lbs	83	42	2.5	11913464
1.1/2"	300/600lbs	95	48	2.5	11913463
1.1/2"	150lbs	86	48	2.5	10001566
2"	150lbs	105	60	2.5	10001556
2"	300/600lbs	111	60	2.5	11913466
2.1/2"	300/600lbs	130	73	2.5	11913467
2.1/2"	150lbs	124	73	2.5	10001568
3"	150lbs	137	89	2.5	10001557
3"	300/600lbs	149	89	3	10001569
4"	150lbs	175	114	2.5	10001558
4"	600lbs	194	114	2.5	11913476
4"	300lbs	181	114	3	10001570
5"	300lbs	216	141	2.5	11913460
5"	150lbs	197	141	2.5	10001559
5"	600lbs	241	141	2.5	11913477
6"	600lbs	267	168	2.5	11913478
6"	150lbs	222	168	2.5	10001560
6"	300lbs	251	168	3	10001571
8"	150lbs	279	219	2.5	10001561
8"	600lbs	321	219	2.5	11913479
8"	300lbs	308	219	2.5	11913461
10"	300lbs	362	273	2.5	11913453
10"	150lbs	340	273	2.5	10001562
10"	600lbs	400	273	2.5	11913469
12"	300lbs	422	324	2.5	11913454
12"	150lbs	410	324	2.5	10001563
12"	600lbs	457	324	2.5	11913470
14"	300lbs	486	356	2.5	11913455
14"	600lbs	492	356	2.5	11913471

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter	Inner diameter	Thickness	Article
		mm	mm	mm	
14"	150lbs	451	356	2.5	11913448
16"	300lbs	540	406	2.5	11913456
16"	150lbs	514	406	2.5	11255892
16"	600lbs	565	406	2.5	11913472
18"	150lbs	549	457	2.5	11913450
18"	600lbs	613	457	2.5	11913473
18"	300lbs	597	457	2.5	11913457
20"	600lbs	683	508	2.5	11913474
20"	300lbs	654	508	2.5	11913458
20"	150lbs	606	508	2.5	11018319
24"	600lbs	791	610	2.5	11913475
24"	150lbs	718	610	2.5	11072516
24"	300lbs	775	610	2.5	11913459

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.