



LEADER Fibre flange gasket FYBAR PT20 ASME B16.21

Characteristics

- Series: FYBAR
- Type: PT20
- Norm: ASME B16.21
- With Inner eyelet: No
- Fibre type: Mineral fibre
- Anti sticking layer: No
- Temperature range: -30 / 130 °C
- Max. pressure: 40 bar
- Suitable for medium: Air (compressed air), Fuels, Grease, Oil

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
1/2"	300/600lbs	54	21	1.5	11589710
1/2"	150lbs	48	21	1.5	11589671
1/2"	150lbs	48	21	2	12259565
1/2"	300/600lbs	54	21	2	12259584
1/2"	300/600lbs	54	21	3	12259657
1/2"	150lbs	48	21	3	12259642
3/4"	150lbs	57	27	1.5	11589672
3/4"	300/600lbs	67	27	1.5	11589711
3/4"	300/600lbs	67	27	2	12259585
3/4"	150lbs	57	27	2	12259566
3/4"	150lbs	57	27	3	12259643
3/4"	300/600lbs	67	27	3	12259658
1"	150lbs	67	33	1.5	11589693
1"	300/600lbs	73	33	1.5	11589712
1"	150lbs	67	33	2	12259567
1"	300/600lbs	73	33	2	12259586
1"	150lbs	67	33	3	11940328
1"	300/600lbs	73	33	3	12259659
1.1/4"	300/600lbs	83	42	1.5	11589713
1.1/4"	150lbs	76	42	1.5	11589694
1.1/4"	150lbs	76	42	2	12259568
1.1/4"	300/600lbs	83	42	2	12259587
1.1/4"	150lbs	76	42	3	12259644
1.1/4"	300/600lbs	83	42	3	12259660
1.1/2"	300/600lbs	95	48	1.5	11589714
1.1/2"	150lbs	86	48	1.5	11589695
1.1/2"	150lbs	86	48	2	12259569
1.1/2"	300/600lbs	95	48	2	12259588
1.1/2"	150lbs	86	48	3	12259645
1.1/2"	300/600lbs	95	48	3	12259661
2"	300/600lbs	111	60	1.5	11589715
2"	150lbs	105	60	1.5	11589696
2"	300/600lbs	111	60	2	12259589
2"	150lbs	105	60	2	12259570
2"	150lbs	105	60	3	11940327
2"	300/600lbs	111	60	3	12259662
2.1/2"	150lbs	124	73	1.5	11589697

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
2.1/2"	300/600lbs	130	73	1.5	11589716
2.1/2"	150lbs	124	73	2	12259571
2.1/2"	300/600lbs	130	73	2	12259590
2.1/2"	300/600lbs	130	73	3	12259663
2.1/2"	150lbs	124	73	3	12259646
3"	150lbs	137	89	1.5	11589698
3"	300/600lbs	149	89	1.5	11589717
3"	300/600lbs	149	89	2	12259591
3"	150lbs	137	89	2	12259572
3"	150lbs	137	89	3	11756162
3"	300/600lbs	149	89	3	12259664
4"	150lbs	175	114	1.5	11589699
4"	300lbs	181	114	1.5	11589718
4"	600lbs	194	114	1.5	12259527
4"	150lbs	175	114	2	12259573
4"	300lbs	181	114	2	12259592
4"	600lbs	194	114	2	12259603
4"	300lbs	181	114	3	12259665
4"	150lbs	175	114	3	11756110
4"	600lbs	194	114	3	12259676
5"	300lbs	216	141	1.5	11589719
5"	150lbs	197	141	1.5	11589700
5"	600lbs	241	141	1.5	12259528
5"	150lbs	197	141	2	12259574
5"	600lbs	241	141	2	12259604
5"	300lbs	216	141	2	12259593
5"	150lbs	197	141	3	12259647
5"	600lbs	241	141	3	12259677
5"	300lbs	216	141	3	12259666
6"	600lbs	267	168	1.5	12259529
6"	300lbs	251	168	1.5	11589720
6"	150lbs	222	168	1.5	11589701
6"	600lbs	267	168	2	12259605
6"	150lbs	222	168	2	12259575
6"	300lbs	251	168	2	12259594
6"	600lbs	267	168	3	12259678
6"	300lbs	251	168	3	12259667
6"	150lbs	222	168	3	12259648
8"	600lbs	321	219	1.5	12259530
8"	300lbs	308	219	1.5	11589721
8"	150lbs	279	219	1.5	11589702
8"	150lbs	279	219	2	12259576
8"	600lbs	321	219	2	12259606
8"	300lbs	308	219	2	12259595
8"	150lbs	279	219	3	12259649
8"	300lbs	308	219	3	12259668
8"	600lbs	321	219	3	12259679
10"	300lbs	362	273	1.5	11589722
10"	150lbs	340	273	1.5	11589703
10"	600lbs	400	273	1.5	12259531
10"	600lbs	400	273	2	12259607
10"	150lbs	340	273	2	12259577
10"	300lbs	362	273	2	12259596

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter	Inner diameter	Thickness	Article
		mm	mm	mm	
10"	600lbs	400	273	3	12259680
10"	300lbs	362	273	3	12259669
10"	150lbs	340	273	3	12259650
12"	600lbs	457	324	1.5	12259532
12"	150lbs	410	324	1.5	11589704
12"	300lbs	422	324	1.5	11589723
12"	600lbs	457	324	2	12259608
12"	300lbs	422	324	2	12259597
12"	150lbs	410	324	2	12259578
12"	150lbs	410	324	3	12259651
12"	300lbs	422	324	3	12259670
12"	600lbs	457	324	3	12259681
14"	600lbs	492	356	1.5	12259533
14"	150lbs	451	356	1.5	11589705
14"	300lbs	486	356	1.5	11589724
14"	150lbs	451	356	2	12259579
14"	600lbs	492	356	2	12259609
14"	300lbs	486	356	2	12259598
14"	150lbs	451	356	3	12259652
14"	600lbs	492	356	3	12259682
14"	300lbs	486	356	3	12259671
16"	150lbs	514	406	1.5	11589706
16"	300lbs	540	406	1.5	11589725
16"	600lbs	565	406	1.5	12259534
16"	150lbs	514	406	2	12259580
16"	600lbs	565	406	2	12259610
16"	300lbs	540	406	2	12259599
16"	150lbs	514	406	3	12259653
16"	300lbs	540	406	3	12259672
16"	600lbs	565	406	3	12259683
18"	600lbs	613	457	1.5	12259535
18"	300lbs	597	457	1.5	11589726
18"	150lbs	549	457	1.5	11589707
18"	600lbs	613	457	2	12259611
18"	150lbs	549	457	2	12259581
18"	300lbs	597	457	2	12259600
18"	600lbs	613	457	3	12259684
18"	300lbs	597	457	3	12259673
18"	150lbs	549	457	3	12259654
20"	600lbs	683	508	1.5	12259536
20"	300lbs	654	508	1.5	11589727
20"	150lbs	606	508	1.5	11589708
20"	150lbs	606	508	2	12259582
20"	300lbs	654	508	2	12259601
20"	600lbs	683	508	2	12259612
20"	300lbs	654	508	3	12259674
20"	150lbs	606	508	3	12259655
20"	600lbs	683	508	3	12259685
24"	600lbs	791	610	1.5	12259537
24"	300lbs	775	610	1.5	11589728
24"	150lbs	718	610	1.5	11589709
24"	300lbs	775	610	2	12259602
24"	150lbs	718	610	2	12259583

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter	Inner diameter	Thickness	Article
		mm	mm	mm	
24"	600lbs	791	610	2	12259613
24"	600lbs	791	610	3	12259686
24"	300lbs	775	610	3	12259675
24"	150lbs	718	610	3	12259656

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.