



FRENZELIT Fibre sealing sheet NOVAPRESS 815

Characteristics

Series: NOVAPRESS

Type: 815

Fibre type: Aramid

Anti sticking layer: No

Temperature range: -50 / 150 °C

Max. pressure: 50 bar

Suitable for medium: Solvents, Refrigerants, Air
(compressed air), Biodiesel, Natural gas, Oil, Weak
Alkalis, Grease, Fuels, Weak Acids, Lubricant

Approval according to: DVGW W270, DVGW, GL

Thickness mm	Length mm	Width mm	Article
0.4	1500	1500	10017327
0.5	1500	1500	10017328
0.75	1500	1500	10017329
1	1500	1500	10017330
1.5	3000	1500	10017336
1.5	1500	1500	10017331
2	1500	1500	10017332
2	3000	1500	10017337
2.5	1500	1500	10017333
3	3000	1500	10017338
3	1500	1500	10017334
4	1500	1500	10017335
4	3000	1500	10017339

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.