



FRENZELIT Fibre sealing sheet NOVAPRESS MULTI

Characteristics

Series: NOVAPRESS

Type: MULTI

Fibre type: Aramid, Graphite

Anti sticking layer: Yes

Temperature range: -100 / 250 °C

Max. pressure: 100 bar

Characteristics [2]

Suitable for medium: Refrigerants, Low pressure steam, Air (compressed air), Oil, Weak Alkalis, Solvents, Weak Acids, Fuels, Natural gas, Lubricant, Grease, Biodiesel, Hydrocarbons

Approval according to: DVGW, BAM, GL, TA-Luft, BS7531 Grade X

Thickness mm	Length mm	Width mm	Article
0.25	1500	1500	10017340
0.3	1500	1500	10017341
0.4	1500	1500	10017342
0.5	1500	1500	10017343
0.7	1500	1500	10017344
1	1500	1500	10017345
1.5	1500	1500	10017346
2	3000	1500	11015114
2	1500	1500	10017347
2.5	1500	1500	10017348
3	3000	1500	10017352
3	1500	1500	10017349
4	1500	1500	10017350
5	1500	1500	10017351

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.