



LEADER Fibre sealing sheet FYBAR PT50

Characteristics

Series: FYBAR

Type: PT50

Fibre type: Aramid

Anti sticking layer: Yes

Temperature range: -30 / 200 °C

Max. pressure: 85 bar

Characteristics [2]

Suitable for medium: Weak Acids, Low pressure steam, Grease, Lubricant, Natural gas, Weak Alkalis, Air (compressed air), Solvents, Biodiesel, Refrigerants, Oil, Potable water, Fuels

Approval according to: DIN30653, Blow out VDI2200, UBA Elastomerleitlinie, BS7531 Grade Y, TA-Luft, DVGW W270, DVGW, HTB DIN30653, GL

Thickness mm	Length mm	Width mm	Article
0.3	1500	1500	11259214
0.5	1500	1500	10017295
0.75	1500	1500	11140657
1	3000	1500	12921494
1.5	3000	1500	12921495
1.5	1500	1500	10017297
2	3000	1500	12921496
2	1500	1500	10017298
3	1500	1500	10017299
3	3000	1500	12921497
4	1500	1500	10017300

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.