



LEADER Graphite sealing sheet EGRAFLEX GHE

Characteristics

Series: EGRAFLEX
Type: GHE
Graphite purity: ≥98 %
Ash content %: ≤2 %
Insert material: RVS 316 L [1.4404]
Insert type: Tanged
Number of inserts: 1
Temperature range: -200 / 450 °C
Max. pressure: 100 bar

Characteristics [2]

Suitable for medium: Fuels, Air [compressed air], Oil, Hydrocarbons, Weak Acids, Natural gas, Low pressure steam, Weak Alkalis, Chlorine, gaseous [7782-50-5], Biodiesel, Lubricant, Solvents, Refrigerants, Cryogenic, Chlorine Water < 5% [7782-50-5], Grease

Thickness mm	Length mm	Width mm	Article
1	1500	1500	10016669
1.5	1500	1500	10016673
1.5	1000	1000	10016670
2	1000	1000	10016671
2	1500	1500	10016674
3	1500	1500	10016675
3	1000	1000	10016672

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.