



SGL Carbon Graphite sealing sheet SIGRAFLEX ECONOMY

Characteristics

Series: SIGRAFLEX
Type: ECONOMY
Graphite purity: ≥98 %
Ash content %: ≤2 %
Insert material: RVS 316 L [1.4404]
Insert type: Foil
Number of inserts: 1
Temperature range: -200 / 450 °C
Max. pressure: 130 bar

Characteristics [2]

Suitable for medium: Lubricant, Food & Beverages, Chlorine Water < 5% [7782-50-5], Weak Alkalis, Refrigerants, Cryogenic, Air (compressed air), Weak Acids, Grease, Biodiesel, Solvents, Hydrocarbons, Oil, Chlorine, gaseous [7782-50-5], Natural gas, Fuels
Approval according to: BAM

Thickness mm	Length mm	Width mm	Article
0.75	1000	1000	10016684
1	1000	1000	10016685
1.5	1000	1000	10016686
2	1000	1000	10016687
2	1000	1000	12940823
3	1000	1000	10016688

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.