


FRENZELIT Graphite sealing sheet NOVAPHIT MST XP



Characteristics

Series: NOVAPHIT
Type: MST XP
Graphite purity: >99.5 %
Insert material: RVS 316 L [1.4404]
Insert type: Expanded mesh
Number of inserts: 7
Temperature range: -200 / 450 °C
Max. pressure: 250 bar

Characteristics [2]

Suitable for medium: Chlorine, gaseous [7782-50-5], Oil, Fuels, Hydrocarbons, Chlorine Water < 5% [7782-50-5], Weak Alkalis, Refrigerants, Low pressure steam, Air [compressed air], Lubricant, Natural gas, Grease, Solvents, Biodiesel, Weak Acids, Cryogenic, Food & Beverages
Approval according to: BAM, FIRE-SAFE ISO 10497, TA-Luft, DVGW, Blow out VDI2200

Thickness mm	Length mm	Width mm	Article
2	1000	1000	12659102
3	1000	1000	11658103

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.