



GARLOCK PTFE sealing sheet GYLON 3501

Characteristics

Series: GYLON

Type: 3501

Material structure: PTFE, modified

Max. temperature: 260 °C

Minimum temperature: -210 °C

Max. pressure: 83 bar

Suitable for medium: Strong acids (except hydrofluoric), Oil, Hydrocarbons, Chlorine Water < 5% (7782-50-5), Weak Acids, Refrigerants, Low pressure steam, Alkalis, Air (compressed air), Fuels, Acids, Chlorine, gaseous (7782-50-5), Cryogenic, Weak Alkalis, Solvents

Approval according to: Blow out VDI2200, BAM, FDA 21 CFR 177.1550, TA-Luft

Marking: Printed

Application

- Recommended in: Chemical, Pharma

Thickness mm	Length mm	Width mm	Article
0.5	750	750	10016806
0.8	750	750	10016807
1	1500	1500	10016808
1.6	1500	1500	10016809
2	1500	1500	10016810
3.2	1500	1500	10016811
4.8	1500	1500	10016812
6.4	1500	1500	10016813

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.