



LEADER PTFE sealing sheet CLIPPERLON 2120

Characteristics

Series: CLIPPERLON

Type: 2120

Material structure: PTFE, modified

Max. temperature: 240 °C

Minimum temperature: -210 °C

Max. pressure: 85 bar

Suitable for medium: Refrigerants, Acids, Low pressure steam, Strong Alkalis, Food & Beverages, Weak Acids, Solvents, Weak Alkalis, Chlorine, gaseous [7782-50-5], Hydrocarbons, Chlorine Water < 5% [7782-50-5], Air [compressed air], Cryogenic, Alkalis

Approval according to: FDA 21 CFR 177.1550, Pamphlet 95 (CI), TA-Luft, EC1935 (10/2011), Blow out VDI2200

Marking: Printed

Application

- Recommended in: Chemical

Thickness mm	Length mm	Width mm	Article
1.5	1500	1500	11917140
2	1500	1500	11917141
3	1500	1500	11917142

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.