


LEADER Graphite flange gasket EGRAFLEX SPG EN 1514-1 IBC

**Characteristics**

Series: EGRAFLEX
Type: SPG
Norm: EN 1514-1 IBC
Graphite purity: 98 %
Insert material: RVS 316 L [1.4404]
Insert type: Tanged
Number of inserts: 1
Anti-stick: No
Temperature range: -200 / 450 °C
Max. pressure: 150 bar

Characteristics [2]

Suitable for medium: Chlorine Water < 5% [7782-50-5], Grease, Weak Alkalis, Air (compressed air), Hydrocarbons, Oil, Fuels, Chlorine, gaseous [7782-50-5], Solvents, Cryogenic, Weak Acids, Biodiesel, Refrigerants, Low pressure steam, Lubricant, Natural gas

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN15	PN10/40	51	22	1.5	12255168
DN15	PN10/40	51	22	3	12255271
DN20	PN10/40	61	27	1.5	12255169
DN20	PN10/40	61	27	3	12255272
DN25	PN10/40	71	34	1.5	12255170
DN25	PN10/40	71	34	3	12255273
DN32	PN10/40	82	43	1.5	12255171
DN32	PN10/40	82	43	3	12255274
DN40	PN10/40	92	49	1.5	12255172
DN40	PN10/40	92	49	3	12255275
DN50	PN10/40	107	61	1.5	12255173
DN50	PN10/40	107	61	3	12255276
DN65	PN10/40	127	77	1.5	12255174
DN65	PN10/40	127	77	3	12255277
DN80	PN10/40	142	89	1.5	12255175
DN80	PN10/40	142	89	3	12255278
DN100	PN10/16	162	115	1.5	12255176
DN100	PN10/16	162	115	3	12255279
DN100	PN25/40	168	115	1.5	12255194
DN100	PN25/40	168	115	3	12255297
DN125	PN10/16	192	141	1.5	12255177
DN125	PN10/16	192	141	3	12255280
DN125	PN25/40	194	141	1.5	12255195
DN125	PN25/40	194	141	3	12255298
DN150	PN10/16	218	169	1.5	12255178
DN150	PN10/16	218	169	3	12255281
DN150	PN25/40	224	169	1.5	12255196
DN150	PN25/40	224	169	3	12255299
DN200	PN10/16	273	220	1.5	12255179
DN200	PN10/16	273	220	3	12255282
DN200	PN25	284	220	1.5	12255197
DN200	PN25	284	220	3	12255300
DN200	PN40	290	220	1.5	12255205
DN200	PN40	290	220	2	11302021
DN200	PN40	290	220	3	12255308
DN250	PN10	328	273	1.5	12255180
DN250	PN10	328	273	3	12255283

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN250	PN16	329	273	1.5	12255187
DN250	PN16	329	273	2	11322068
DN250	PN16	329	273	3	12255290
DN250	PN25	340	273	1.5	12255198
DN250	PN25	340	273	3	12255301
DN250	PN40	352	273	1.5	12255206
DN250	PN40	352	273	2	11322083
DN250	PN40	352	273	3	12255309
DN300	PN10	378	324	1.5	12255181
DN300	PN10	378	324	3	12255284
DN300	PN16	384	324	1.5	12255188
DN300	PN16	384	324	3	12255291
DN300	PN25	400	324	1.5	12255199
DN300	PN25	400	324	3	12255302
DN300	PN40	417	324	1.5	12255207
DN300	PN40	417	324	2	11322084
DN300	PN40	417	324	3	12255310
DN350	PN10	438	356	1.5	12255182
DN350	PN10	438	356	3	12255285
DN350	PN16	444	356	1.5	12255189
DN350	PN16	444	356	2	11322070
DN350	PN16	444	356	3	12255292
DN350	PN25	457	356	1.5	12255200
DN350	PN25	457	356	3	12255303
DN350	PN40	474	356	1.5	12255208
DN350	PN40	474	356	2	11322085
DN350	PN40	474	356	3	12255311
DN400	PN10	489	407	1.5	12255183
DN400	PN10	489	407	3	12255286
DN400	PN16	495	407	1.5	12255190
DN400	PN16	495	407	2	11322071
DN400	PN16	495	407	3	12255293
DN400	PN25	514	407	1.5	12255201
DN400	PN25	514	407	3	12255304
DN400	PN40	546	407	1.5	12255209
DN400	PN40	546	407	2	11322086
DN400	PN40	546	407	3	12255312
DN450	PN10	539	458	1.5	12255184
DN450	PN10	539	458	3	12255287
DN450	PN16	555	458	1.5	12255191
DN450	PN16	555	458	2	11322072
DN450	PN16	555	458	3	12255294
DN450	PN25	564	458	1.5	12255202
DN450	PN25	564	458	3	12255305
DN450	PN40	571	458	1.5	12255210
DN450	PN40	571	458	2	11322087
DN450	PN40	571	458	3	12255313
DN500	PN10	594	508	1.5	12255185
DN500	PN10	594	508	3	12255288
DN500	PN16	617	508	1.5	12255192
DN500	PN16	617	508	2	11322073
DN500	PN16	617	508	3	12255295
DN500	PN25	624	508	1.5	12255203

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter	Inner diameter	Thickness	Article
		mm	mm	mm	
DN500	PN25	624	508	3	12255306
DN500	PN40	628	508	1.5	12255211
DN500	PN40	628	508	2	11322088
DN500	PN40	628	508	3	12255314
DN600	PN10	695	610	1.5	12255186
DN600	PN10	695	610	3	12255289
DN600	PN16	734	610	1.5	12255193
DN600	PN16	734	610	2	11322074
DN600	PN16	734	610	3	12255296
DN600	PN25	734	610	1.5	12255204
DN600	PN25	734	610	3	12255307
DN600	PN40	747	610	1.5	12255212
DN600	PN40	747	610	2	11322089
DN600	PN40	747	610	3	12255315

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.