


LEADER PTFE flange gasket CLIPPERLON 2110 EN 1514-1

**Characteristics****Series:** CLIPPERLON**Type:** 2110**Norm:** EN 1514-1 IBC**Material structure:** PTFE, modified**Marking:** Printed**Temperature range:** -210 / 240 °C**Max. pressure:** 40 bar**Suitable for medium:** Chlorine Water < 5%

[7782-50-5], Weak Acids, Chlorine, gaseous
 [7782-50-5], Food & Beverages, Alkalis, Acids,
 Cryogenic, Fuels, Refrigerants, Weak Alkalis,
 Solvents, Air (compressed air), Low pressure steam,
 Hydrocarbons

Approval according to: TA-Luft, EC1935 [10/2011], FDA
 21 CFR 177.1550, WRAS, Blow out VDI2200

Application

- Recommended in: Chemical, Food & Beverages

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN10	PN10/40	46	18	1.5	12565744
DN10	PN10/40	46	18	2	12037692
DN10	PN10/40	46	18	3	12336985
DN15	PN10/40	51	22	1.5	12257524
DN15	PN10/40	51	22	2	11934242
DN15	PN10/40	51	22	3	12257648
DN20	PN10/40	61	27	2	11934243
DN20	PN10/40	61	27	3	12257649
DN20	PN10/40	61	27	1.5	12257525
DN25	PN10/40	71	34	1.5	12257526
DN25	PN10/40	71	34	2	11934244
DN25	PN10/40	71	34	3	12257650
DN32	PN10/40	82	43	1.5	12257527
DN32	PN10/40	82	43	2	11934245
DN32	PN10/40	82	43	3	12257651
DN40	PN10/40	92	49	2	11934246
DN40	PN10/40	92	49	1.5	12257528
DN40	PN10/40	92	49	3	12257652
DN50	PN10/40	107	61	1.5	12257529
DN50	PN10/40	107	61	2	11934247
DN50	PN10/40	107	61	3	12257653
DN65	PN10/40	127	77	2	11934248
DN65	PN10/40	127	77	3	12257654
DN65	PN10/40	127	77	1.5	12257530
DN80	PN10/40	142	89	1.5	12257531
DN80	PN10/40	142	89	2	11934249
DN80	PN10/40	142	89	3	12257655
DN100	PN10/16	162	115	1.5	12258192
DN100	PN25/40	168	115	2	12037693
DN100	PN10/16	162	115	2	11934238
DN100	PN25/40	168	115	3	12257674
DN100	PN10/16	162	115	3	12257656
DN100	PN25/40	168	115	1.5	12258206
DN125	PN10/16	192	141	1.5	12949958
DN125	PN10/16	192	141	2	11934239
DN125	PN10/16	192	141	3	12257657
DN125	PN25/40	194	141	1.5	12949959

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN125	PN25/40	194	141	2	12037694
DN125	PN25/40	194	141	3	12257675
DN150	PN10/16	218	169	1.5	12258204
DN150	PN10/16	218	169	2	11934240
DN150	PN10/16	218	169	3	12257658
DN150	PN25/40	224	169	1.5	12258208
DN150	PN25/40	224	169	2	12037695
DN150	PN25/40	224	169	3	12257676
DN200	PN10/16	273	220	1.5	12258205
DN200	PN25	284	220	1.5	12257553
DN200	PN40	290	220	1.5	12257561
DN200	PN10/16	273	220	2	11934241
DN200	PN25	284	220	2	12257586
DN200	PN40	290	220	3	12257685
DN200	PN25	284	220	3	12257677
DN200	PN10/16	273	220	3	12257659
DN200	PN40	290	220	2	12037696
DN250	PN16	329	273	1.5	12257543
DN250	PN25	340	273	1.5	12257554
DN250	PN10	328	273	1.5	12257536
DN250	PN10	328	273	2	11934237
DN250	PN40	352	273	2	12037698
DN250	PN25	340	273	2	12257587
DN250	PN16	329	273	2	12037697
DN250	PN16	329	273	3	12257667
DN250	PN40	352	273	3	12257686
DN250	PN25	340	273	3	12257678
DN250	PN10	328	273	3	12257660
DN250	PN40	352	273	1.5	12257562
DN300	PN10	378	324	1.5	12257537
DN300	PN25	400	324	1.5	12257555
DN300	PN16	384	324	1.5	12257544
DN300	PN40	417	324	2	12037699
DN300	PN16	384	324	2	12257582
DN300	PN10	378	324	2	11934250
DN300	PN25	400	324	2	12257588
DN300	PN25	400	324	3	12257679
DN300	PN16	384	324	3	12257668
DN300	PN10	378	324	3	12257661
DN300	PN40	417	324	1.5	12257563
DN300	PN40	417	324	3	12257687
DN350	PN16	444	356	1.5	12257545
DN350	PN25	457	356	1.5	12257556
DN350	PN40	474	356	1.5	12257564
DN350	PN10	438	356	1.5	12257538
DN350	PN10	438	356	2	11934251
DN350	PN40	474	356	2	12257594
DN350	PN16	444	356	2	12257583
DN350	PN25	457	356	2	12257589
DN350	PN25	457	356	3	12257680
DN350	PN16	444	356	3	12257669
DN350	PN10	438	356	3	12257662
DN350	PN40	474	356	3	12257688

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN400	PN16	495	407	1.5	12257546
DN400	PN25	514	407	1.5	12257557
DN400	PN40	546	407	1.5	12257565
DN400	PN10	489	407	1.5	12257539
DN400	PN16	495	407	2	12037700
DN400	PN10	489	407	2	11934252
DN400	PN25	514	407	2	12257590
DN400	PN25	514	407	3	12257681
DN400	PN40	546	407	3	12257689
DN400	PN10	489	407	3	12257663
DN400	PN16	495	407	3	12257670
DN400	PN40	546	407	2	12257595
DN450	PN10	539	458	1.5	12257540
DN450	PN16	555	458	1.5	12257547
DN450	PN25	564	458	1.5	12257558
DN450	PN25	564	458	2	12257591
DN450	PN10	539	458	2	11934253
DN450	PN16	555	458	2	12037701
DN450	PN16	555	458	3	12257671
DN450	PN25	564	458	3	12257682
DN450	PN10	539	458	3	12257664
DN450	PN40	571	458	1.5	12257566
DN450	PN40	571	458	2	12257596
DN450	PN40	571	458	3	12257690
DN500	PN16	617	508	1.5	12257548
DN500	PN10	594	508	1.5	12257541
DN500	PN40	628	508	1.5	12257567
DN500	PN25	624	508	1.5	12257559
DN500	PN40	628	508	2	12257597
DN500	PN10	594	508	2	11934254
DN500	PN16	617	508	2	12257584
DN500	PN25	624	508	2	12257592
DN500	PN40	628	508	3	12257691
DN500	PN10	594	508	3	12257665
DN500	PN25	624	508	3	12257683
DN500	PN16	617	508	3	12257672
DN600	PN10	695	610	1.5	12257542
DN600	PN40	747	610	1.5	12257568
DN600	PN25	731	610	1.5	12257560
DN600	PN16	734	610	1.5	12257549
DN600	PN25	731	610	2	12257593
DN600	PN16	734	610	2	12257585
DN600	PN10	695	610	2	11934255
DN600	PN10	695	610	3	12257666
DN600	PN40	747	610	3	12257692
DN600	PN16	734	610	3	12257673
DN600	PN25	731	610	3	12257684
DN600	PN40	747	610	2	12257598

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.