


LEADER PTFE flange gasket CLIPPERLON 2100 EN 1514-1

**Characteristics****Series:** CLIPPERLON**Type:** 2100**Norm:** EN 1514-1 IBC**Material structure:** PTFE, modified**Marking:** Printed**Temperature range:** -240 / 240 °C**Max. pressure:** 85 bar

Suitable for medium: Alkalis, Air (compressed air), Low pressure steam, Cryogenic, Acids, Refrigerants, Food & Beverages, Weak Acids, Chlorine, gaseous [7782-50-5], Chlorine Water < 5% [7782-50-5], Solvents, Hydrocarbons, Strong acids (except hydrofluoric), Potable water, Weak Alkalis

Approval according to: TA-Luft, FDA 21 CFR 177.1550, Blow out VDI2200, EC1935 (10/2011)

Application

- Recommended in: Chemical, Food & Beverages

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN10	PN10/40	46	18	1.5	12968525
DN10	PN10/40	46	18	2	12968526
DN10	PN10/40	46	18	3	12968527
DN15	PN10/40	51	22	1.5	12968528
DN15	PN10/40	51	22	2	11934297
DN15	PN10/40	51	22	3	12968529
DN20	PN10/40	61	27	1.5	12968530
DN20	PN10/40	61	27	2	11934298
DN20	PN10/40	61	27	3	12968531
DN25	PN10/40	71	34	1.5	12968532
DN25	PN10/40	71	34	2	11934299
DN25	PN10/40	71	34	3	12968533
DN32	PN10/40	82	43	1.5	12968534
DN32	PN10/40	82	43	2	11934300
DN32	PN10/40	82	43	3	12968535
DN40	PN10/40	92	49	1.5	12968536
DN40	PN10/40	92	49	2	11934301
DN40	PN10/40	92	49	3	12968537
DN50	PN10/40	107	61	1.5	12968538
DN50	PN10/40	107	61	2	11934302
DN50	PN10/40	107	61	3	12968539
DN65	PN10/40	127	77	1.5	12968540
DN65	PN10/40	127	77	2	11934303
DN65	PN10/40	127	77	3	12968541
DN80	PN10/40	142	89	1.5	12968542
DN80	PN10/40	142	89	2	11934304
DN80	PN10/40	142	89	3	12968543
DN100	PN10/16	162	115	1.5	12968517
DN100	PN25/40	168	115	1.5	12968583
DN100	PN10/16	162	115	2	11934293
DN100	PN25/40	168	115	2	12968584
DN100	PN25/40	168	115	3	12968585
DN100	PN10/16	162	115	3	12968518
DN125	PN10/16	192	141	1.5	12968519
DN125	PN25/40	194	141	1.5	12968586
DN125	PN25/40	194	141	2	12968587
DN125	PN10/16	192	141	2	11934294

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN125	PN10/16	192	141	3	12968520
DN125	PN25/40	194	141	3	12968588
DN150	PN10/16	218	169	1.5	12968521
DN150	PN25/40	224	169	1.5	12968589
DN150	PN25/40	224	169	2	12968590
DN150	PN10/16	218	169	2	11934295
DN150	PN25/40	224	169	3	12968591
DN150	PN10/16	218	169	3	12968522
DN200	PN10/16	273	220	1.5	12968523
DN200	PN40	290	220	1.5	12968592
DN200	PN25	284	220	1.5	12968562
DN200	PN25	284	220	2	12968563
DN200	PN10/16	273	220	2	11934296
DN200	PN40	290	220	2	12968593
DN200	PN10/16	273	220	3	12968524
DN200	PN40	290	220	3	12968594
DN200	PN25	284	220	3	12968564
DN250	PN16	329	273	1.5	12968544
DN250	PN10	328	273	1.5	12968505
DN250	PN40	352	273	1.5	12968595
DN250	PN25	340	273	1.5	12968565
DN250	PN25	340	273	2	12968566
DN250	PN10	328	273	2	11934292
DN250	PN40	352	273	2	12968596
DN250	PN16	329	273	2	12968545
DN250	PN16	329	273	3	12968546
DN250	PN10	328	273	3	12968506
DN250	PN25	340	273	3	12968567
DN250	PN40	352	273	3	12968597
DN300	PN16	384	324	1.5	12968547
DN300	PN10	378	324	1.5	12968507
DN300	PN40	417	324	1.5	12968598
DN300	PN25	400	324	1.5	12968568
DN300	PN40	417	324	2	12968599
DN300	PN10	378	324	2	11934305
DN300	PN25	400	324	2	12968569
DN300	PN16	384	324	2	12968548
DN300	PN40	417	324	3	12968600
DN300	PN10	378	324	3	12968508
DN300	PN25	400	324	3	12968570
DN300	PN16	384	324	3	12968549
DN350	PN16	444	356	1.5	12968550
DN350	PN25	457	356	1.5	12968571
DN350	PN10	438	356	1.5	12968509
DN350	PN40	474	356	1.5	12968601
DN350	PN16	444	356	2	12968551
DN350	PN10	438	356	2	11934306
DN350	PN25	457	356	2	12968572
DN350	PN40	474	356	2	12968602
DN350	PN16	444	356	3	12968552
DN350	PN40	474	356	3	12968603
DN350	PN10	438	356	3	12968510
DN350	PN25	457	356	3	12968573

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN400	PN40	546	407	1.5	12968604
DN400	PN10	489	407	1.5	12968511
DN400	PN25	514	407	1.5	12968574
DN400	PN16	495	407	1.5	12968553
DN400	PN40	546	407	2	12968605
DN400	PN25	514	407	2	12968575
DN400	PN16	495	407	2	12968554
DN400	PN10	489	407	2	11934307
DN400	PN25	514	407	3	12968576
DN400	PN40	546	407	3	12968606
DN400	PN16	495	407	3	12968555
DN400	PN10	489	407	3	12968512
DN450	PN10	539	458	2	11934308
DN500	PN10	594	508	1.5	12968513
DN500	PN25	624	508	1.5	12968577
DN500	PN16	617	508	1.5	12968556
DN500	PN40	628	508	1.5	12968607
DN500	PN16	617	508	2	12968557
DN500	PN40	628	508	2	12968608
DN500	PN25	624	508	2	12968578
DN500	PN10	594	508	2	11934309
DN500	PN40	628	508	3	12968609
DN500	PN10	594	508	3	12968514
DN500	PN25	624	508	3	12968579
DN500	PN16	617	508	3	12968558
DN600	PN10	695	610	1.5	12968515
DN600	PN25	731	610	1.5	12968580
DN600	PN16	734	610	1.5	12968559
DN600	PN40	747	610	1.5	12968610
DN600	PN40	747	610	2	12968611
DN600	PN10	695	610	2	11934310
DN600	PN25	731	610	2	12968581
DN600	PN16	734	610	2	12968560
DN600	PN10	695	610	3	12968516
DN600	PN40	747	610	3	12968612
DN600	PN25	731	610	3	12968582
DN600	PN16	734	610	3	12968561

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.