


LEADER Graphite flange gasket EGRAFLEX GHE ASME B16.21



Characteristics

Series: EGRAFLEX

Type: GHE

Norm: ASME B16.21

Graphite purity: >98 %

Insert material: RVS 316 L [1.4404]

Insert type: Tanged

Number of inserts: 1

Anti-stick: No

Temperature range: -200 / 450 °C

Max. pressure: 100 bar

Characteristics [2]

Suitable for medium: Lubricant, Biodiesel, Chlorine, gaseous [7782-50-5], Solvents, Natural gas, Oil, Cryogenic, Fuels, Weak Alkalis, Hydrocarbons, Low pressure steam, Air [compressed air], Refrigerants, Grease, Chlorine Water < 5% [7782-50-5], Weak Acids

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
1/2"	150lbs	48	21	1.5	10001108
1/2"	300/600lbs	54	21	1.5	10001130
3/4"	150lbs	57	27	1.5	10001109
3/4"	300/600lbs	67	27	1.5	10001131
1"	150lbs	67	33	1.5	10001095
1"	300/600lbs	73	33	1.5	10001127
1.1/4"	150lbs	76	42	1.5	10001031
1.1/4"	300/600lbs	83	42	1.5	11090006
1.1/2"	150lbs	86	48	1.5	10001110
1.1/2"	300/600lbs	95	48	1.5	10001132
2"	150lbs	105	60	1.5	10001096
2"	300/600lbs	111	60	1.5	10001128
2.1/2"	150lbs	124	73	1.5	10001111
2.1/2"	300/600lbs	130	73	1.5	10001133
3"	150lbs	137	89	1.5	10001097
3"	300/600lbs	149	89	1.5	10001129
4"	150lbs	175	114	1.5	10001098
4"	300lbs	181	114	1.5	10001112
5"	150lbs	197	141	1.5	11045603
5"	300lbs	216	141	1.5	11045604
5"	600lbs	241	141	1.5	11913539
6"	150lbs	222	168	1.5	10001099
6"	300lbs	251	168	1.5	10001113
8"	150lbs	279	219	1.5	10001100
8"	300lbs	308	219	1.5	10001114
10"	150lbs	340	273	1.5	10001101
10"	300lbs	362	273	1.5	10001115
12"	150lbs	410	324	1.5	10001102
12"	300lbs	422	324	1.5	10001116
14"	150lbs	451	356	1.5	10001103
14"	300lbs	486	356	1.5	10001117
14"	600lbs	492	356	1.5	11913521
16"	150lbs	514	406	1.5	10001104
16"	300lbs	540	406	1.5	10001118
16"	600lbs	565	406	1.5	11913524
18"	150lbs	549	457	1.5	10001105
18"	300lbs	597	457	1.5	10001119

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter	Inner diameter	Thickness	Article
		mm	mm	mm	
20"	150lbs	606	508	1.5	10001106
20"	300lbs	654	508	1.5	10001120
20"	600lbs	683	508	1.5	11913530
24"	150lbs	718	610	1.5	10001107
24"	300lbs	775	610	1.5	10001121
24"	600lbs	791	610	1.5	11913533

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.