

SGL Carbon Gauge glass seal Sigraflex® HD for reflex glass

Characteristics



Characteristics [2]

Suitable for medium: Chlorine Water < 5% [7782-50-5], Low pressure steam, Air [compressed air], Cryogenic, Grease, Fuels, Weak Alkalis, Chlorine, gaseous [7782-50-5], Hydrocarbons, Oil, Biodiesel, Natural gas, Solvents, Refrigerants, Weak Acids, Lubricant, Food & Beverages

Approval according to: DVGW, EC1935/2004, Blow out VDI2200, BAM, Germanischer Lloyd, FIRE-SAFE API 607, BS6755

Description	Article
Gauge glass seal Sigraflex HD for reflex glass 165x34x17	10057813
Gauge glass seal Sigraflex HD for reflex glass 190x34x17	10057814
Gauge glass seal Sigraflex HD for reflex glass 250x34x17	10057816
Gauge glass seal Sigraflex HD for reflex glass 280x34x17	10057817
Gauge glass seal Sigraflex HD for reflex glass 320x34x17	10057818
Gauge glass seal Sigraflex HD for reflex glass 340x34x17	10057819
Gauge glass seal Sigraflex HD for reflex glass 370x34x17	10057820
Gauge glass seal Sigraflex HD for reflex glass 480x34x17	10057823

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.