



GRUNDFOS Submersible pump Series: SEG - Dompelpomp gietijzer met versnijdingswaaier - (0,9 - 2,6 kW)

Characteristics

Series: SEG

Connection: Flange

Pressure rating flange: PN10

Material pump casing: Cast iron

Material quality: EN-JL1030

Insulation class acc. to IEC: F

Maximum flow rate	Nominal volume flow rate	Max. immersion depth	Supply voltage	Length connecting cord	Rotational speed	Nominal current	Connection size	Pump height	Article
l/min	m³/h	m		m	rpm	A		mm	
7992	8	10	3 x 400-415V AC	10	2750	3	DN40	546	23498555
15012	15	10	1 x 230V AC	10	2890	6	DN40	546	23498549
15012	15	10	1 x 230V AC	10	2890	6	DN40	546	23498548
15984	16	10	3 x 400-415V AC	10	2860	3	DN40	546	23498551
15984	16	10	3 x 400-415V AC	10	2860	3	DN40	546	23498550
18000	18	10	1 x 230V AC	10	2820	8	DN40	546	23498553
18000	18	10	1 x 230V AC	10	2820	8	DN40	546	23498552
18000	18	10	3 x 400-415V AC	10	2900	7	DN40	652	23498560
18000	18	10	3 x 400-415V AC	10	2900	7	DN40	652	23498561
18000	18	10	3 x 400-415V AC	10	2750	3	DN40	546	23498554
19008	19	10	3 x 400-415V AC	10	2700	4	DN40	546	23498557
19008	19	10	3 x 400-415V AC	10	2830	8	DN40	652	23498562
19008	19	10	3 x 400-415V AC	10	2870	6	DN40	614	23498558
19008	19	10	3 x 400-415V AC	10	2700	4	DN40	546	23498556
19008	19	10	3 x 400-415V AC	10	2870	6	DN40	614	23498559

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.