

## Hose Gamma Extra Red, SBR lay flat fire and water hose



### Application

- lay flat fire hose and industrial transport hose
- also suitable as water hose at shipboard, refineries or construction sites

### Temperature range

-30 °C to +80 °C

### Burst pressure

- minimum 30 bar
- safety factor 3:1

### Tube

- black SBR rubber
- smooth

### Cover

- 2 braided polyester fabrics with high tensile strength with red PU coating
- ozone and weather resistant
- oil resistant
- wear resistant

### Approvals/regulations

- DIN 14811 class 2
- prEN 1924 class 3
- BS 6391:2009 type 2
- NEN 2242 MED (wheelmark) module B+D

### Connections

Storz, DSP, Guillemin

### Assembly

stainless steel wire or FIXED hose clamps

| Internal diameter | Wall thickness | Outer diameter | Maximum operating pressure | Minimum burst pressure | Roll length | Weight | Article  |
|-------------------|----------------|----------------|----------------------------|------------------------|-------------|--------|----------|
| mm                | mm             | mm             | bar                        | bar                    | m           | kg/m   |          |
| 25                | 3              | 31             | 20                         | 60                     | 40          | 0.14   | 10015049 |
| 32                | 3              | 38             | 20                         | 60                     | 40          | 0.17   | 11305344 |
| 38                | 3              | 44             | 20                         | 60                     | 40          | 0.21   | 10015050 |
| 45                | 3              | 51             | 20                         | 60                     | 40          | 0.26   | 10015051 |
| 52                | 3              | 58             | 17                         | 50                     | 40          | 0.29   | 10015052 |
| 65                | 3              | 71             | 17                         | 50                     | 40          | 0.36   | 10015053 |
| 70                | 3              | 76             | 17                         | 50                     | 40          | 0.39   | 10015054 |
| 75                | 3              | 81             | 17                         | 50                     | 40          | 0.49   | 10015055 |
| 102               | 4              | 110            | 13                         | 40                     | 40          | 0.65   | 10015056 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

| Internal diameter | Wall thickness | Outer diameter | Maximum operating pressure | Minimum burst pressure | Roll length | Weight | Article  |
|-------------------|----------------|----------------|----------------------------|------------------------|-------------|--------|----------|
| mm                | mm             | mm             | bar                        | bar                    | m           | kg/m   |          |
| 110               | 4              | 118            | 12                         | 35                     | 40          | 0.75   | 10015057 |
| 150               | 4              | 158            | 10                         | 30                     | 40          | 0.95   | 10015058 |
|                   |                |                | 17                         | 50                     | 100         | 0.59   | 14107253 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.