

Hose coupling, with tri-clamp connection type SHTC



- Characteristics**
- Type of component:** Hose tail coupling
 - Material:** Stainless steel (AISI 316)
 - Connection type:** Triclamp
 - Hose fitting type:** Triclamp DIN 32676
 - Connection termination:** ISO
 - Elbow angle [degr.]:** 45 °
 - Hose tail execution:** Serrated, with safety collar
 - Temperature range [°C]:** -10 / 140 °C

Connection termination size	Hose ID (DN)	Maximum operating pressure bar	Maximum operating pressure psi	Article
				13526166
				14201476
				13526169
				13526148
				12698703
				13526150
				14201470
				13526139
				13526154
				13395124
				13526156
				13526168
				13622757
				13562405
				13526151
				14201478
				13506609
				13526157
				13562651
				14201477
				13526177
				13526167
				13526158
				13526143
				13526146
				13526149
				13526140
				13526163
				13526172
				13526176
				13526173
				13526152
				13634189
				12733993
				13526175
				13526147
				14201475
				13562652
				14009928

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Connection termination size	Hose ID (DN)	Maximum operating pressure bar	Maximum operating pressure psi	Article
				11619733
				11181149
				12583418
50,5/ 12,7x1,65 [9,4]	DN12	25	362.5	13526145
34,0/ 21,3x1,6 [18,1]	DN12	25	362.5	13580501
34,0/ 23,0x1,5 [20,0]	DN12	25	362.5	13526144
25/ 13x1,5 [10,0]	DN19	25	362.5	13526159
50,5/ 19,05x1,65 [15,75]	DN20	25	362.5	13543177
50,5/ 38,1x1,65 [34,8]	DN25	25	362.5	13526161
64,0/ 38,1x1,65 [34,8]	DN32	16	232	13562055
32 mm	DN32	25	362.5	13526164
50,5/ 38,1x1,65 [34,8]	DN38	25	362.5	13562371
64,0/ 50,8x1,65 [47,6]	DN38	16	232	13543416
50,5/ 38,1x1,5 [35,1]	DN38	25	362.5	13526170
50,5/ 38,1x1,65 [34,8]	DN38	25	362.5	13543483
64,0/ 38,1x1,65 [34,8]	DN50	16	232	12736665
25/ 8x1 [6,0]	DN06	25	362	11406644
25/ 13x1,5 [10,0]	DN10	25	362.5	13543489
34/ 15x1,5 [12,0]	DN12	25	362	11237978
25/ 13x1,5 [10,0]	DN12	25	362	11376086
50,5/ 29,0x1,5 [26,0]	DN20	25	362.5	13543481
50,5/ 35,0x1,5 [32,0]	DN25	25	362.5	13526160
64,0/ 53,0x1,5 [50,0]	DN25	16	232	11589558
50,5/ 29,0x1,5 [26,0]	DN25	25	362	11277191
50,5/ 41,0x1,5 [38,0]	DN38	25	362	12144035
64,0/ 53,0x1,5 [50,0]	DN38	16	232	13580464
64,0/ 53,0x1,5 [50,0]	DN50	16	232	11589559
106,0/ 85,0x2,0 [81,0]	DN75	10	145	11181150
119,0/ 104,0x2,0 [100,0]	DN100	10	145	11480129
50,5/ 12,7x1,65 [9,4]	DN12	25	362.5	14261165
50,5/ 12,7x1,65 [9,4]	DN12	25	362	11623847
50,5/ 25,4x1,65 [22,1]	DN12	25	362	11181123
25/ 19,05x1,65 [15,75]	DN12	25	362	11387234
25/ 12,7x1,65 [9,4]	DN12	25	362	11181082
25/ 12,7x1,65 [9,4]	DN16	25	362	11204081
50,5/ 19,05x1,65 [15,75]	DN19	25	362	11352162
25/ 19,05x1,65 [15,75]	DN19	25	362	12133106
34,0/ 19,05x1,65 [15,75]	DN19	25	362	11181125
25/ 12,7x1,65 [9,4]	DN19	25	362	11181124
25/ 19,05x1,65 [15,75]	DN20	25	362	11311026
25/ 19,05x1,65 [15,75]	DN25	25	362	11410018
50,5/ 25,4x1,65 [22,1]	DN25	25	232	11181129
OD 50.5 - ID 22.6 mm	DN25	25	362	12463461
50,5/ 38,1x1,65 [34,8]	DN38	25	362	11385978
50,5/ 38,1x1,65 [34,8]	DN38	25	362	11181143
77,0/ 63,5x1,65 [60,2]	DN65	16	232	12658695
50,5/ 25,4x1,25 [22,9]	DN12	25	362	11339214
50,5/ 38,1x1,5 [35,1]	DN19	25	362	11339213
25/ 19,05x1,65 [15,75]	DN20	25	362.5	12733979
50,5/ 38,1x1,5 [35,1]	DN25	25	362	11589561
50,5/ 25,4x1,25 [22,9]	DN25	25	362	11589560
50,5/ 38,1x1,5 [35,1]	DN32	25	362	11456324
64,0/ 50,8x1,5 [47,8]	DN38	16	232	12486548

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Connection termination size	Hose ID (DN)	Maximum operating pressure		Article
		bar	psi	
64,0/ 50,8x1,5 [47,8]	DN38	16	232	13526171
77,0/ 63,5x1,65 [60,2]	DN50	16	362.5	13580445
34,0/ 17,2x1,6 [14,0]	DN10	25	362.5	13627780
OD 50.5 - ID 35.1 mm	DN19	25	362	11455047
64,0/ 48,3x2,0 [44,3]	DN19	16	232	12369078
50,5/ 26,6x1,6 [23,7]	DN19	25	362	11181126
50,5/ 21,3x1,6 [18,1]	DN19	25	362	11443969
50,5/ 26,6x1,6 [23,7]	DN32	25	362	11181131
50,5/ 41,0x1,5 [38,0]	DN32	25	362.5	13580458
50,5/ 33,7x2,0 [29,7]	DN32	25	362.5	13526165
64,0/ 48,3x2,0 [44,3]	DN38	16	232	11181144
64,0/ 48,3x2,0 [44,3]	DN50	16	232	11209033
OD 77.0 - ID 63.5 mm	DN65	16	232	11181148

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.