



GF Butterfly valve Series: 567 PVC-U/PVC-U Double-eccHandle Wafer type

Characteristics

Series: 567

Norm: EN (DIN)

Valve design: Double-eccentric

Housing material: PVC-U

Connection: Wafer type

Face to Face norm: Manufacturer standard

Operation: Handle

Disk material: PVC-U

Primary spindle seal material: FPM (FKM)

Nominal inner diameter	Pressure rating	Pressure rating flange	Face to Face length	Material liner	Spindle material	Quality class spindle	Minimum medium temperature [continuous]	Maximum medium temperature [continuous]	Article
			mm				°C	°C	
DN50	PN10	PN10	45	EPDM	Stainless steel	1.4000	0	60	11380162
DN50	PN10	PN10	45	FPM (FKM)	Stainless steel	1.4000	0	60	11383491
DN65	PN10	PN10	46	EPDM	Stainless steel	1.4000	0	60	11381183
DN65	PN10	PN10	46	FPM (FKM)	Stainless steel	1.4000	0	60	11383527
DN80	PN10	PN10	49	EPDM	Stainless steel	1.4000	0	60	11381189
DN80	PN10	PN10	49	FPM (FKM)	Stainless steel	1.4000	0	60	11383530
DN100	PN10	PN10	56	EPDM	Stainless steel	1.4000	0	60	11382974
DN100	PN10	PN10	56	FPM (FKM)	Stainless steel	1.4000	0	60	11383531
DN125	PN10	PN10	64	EPDM	Stainless steel	1.4000	0	60	11377233
DN125	PN10	PN10	64	FPM (FKM)	Stainless steel	1.4000	0	60	11383532
DN150	PN10	PN10		FPM (FKM)	Stainless steel	1.4021			11383533
DN150	PN10	PN10	72	EPDM	Stainless steel	1.4000	0	60	11382965
DN200	PN10	PN10	73	EPDM	Stainless steel	1.4000	0	60	11382976
DN200	PN10	PN10	73	FPM (FKM)	Stainless steel	1.4000	0	60	11383534

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.