


LEADER Spiral-wound gasket SRI 316L/316L/C/316L ASME B16.20



Characteristics

Series: SRI

Type: Spiral with inside and outside ring

Norm: ASME B16.20B

Inside ring material: Stainless steel 316L

Spiral material: Stainless steel 316L

Material filler: Graphite 98%

Centring ring material: Stainless steel 316L

Temperature range: -200 / 450 °C

Characteristics [2]

Suitable for medium: Biodiesel, Cryogenic, Gases, Natural gas, Refrigerants, High pressure steam, Moderate Acids, Aqueous solutions, Chemicals, Lubricant, Weak Acids, Oil, Alkalis, Steam, Acids, Caustics, Water (process water), Grease, Air (compressed air), Weak Alkalis, Low pressure steam, Hydrocarbons, Solvents, Water, Fuels, Fuel oil

Approval according to: TA-Luft, BAM, EN10.204 3.1, Fire safe

Spiral ring thickness: 4.5 mm

Inside ring thickness: 3 mm

Flange pressure stage	Nominal diameter	Article
150lbs	1.1/2"	11400246
300/600lbs	1.1/2"	11400265
900/1500lbs	1.1/2"	11536809
2500lbs	1.1/2"	12332467
150lbs	1.1/4"	11400245
300/600lbs	1.1/4"	11400264
150lbs	1/2"	11400242
300/600lbs	1/2"	11400261
900/1500lbs	1/2"	11536807
2500lbs	1/2"	11534583
150lbs	1"	11400244
300/600lbs	1"	11400263
900/1500lbs	1"	11619838
2500lbs	1"	12139317
150lbs	2.1/2"	11400248
300/600lbs	2.1/2"	11400267
2500lbs	2.1/2"	12563475
150lbs	2"	11400247
300/600lbs	2"	11400266
900/1500lbs	2"	11619839
2500lbs	2"	11536819
150lbs	3/4"	11400243
300/600lbs	3/4"	11400262
900/1500lbs	3/4"	11592733
2500lbs	3/4"	12563474
150lbs	3"	11400249
300/600lbs	3"	11400268
900lbs	3"	11536799
1500lbs	3"	11536810
2500lbs	3"	11536821
150lbs	4"	11400250
300lbs	4"	11400269
600lbs	4"	11400280

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Flange pressure stage	Nominal diameter	Article
900lbs	4"	11536800
1500lbs	4"	11536812
150lbs	5"	11400251
300lbs	5"	11400270
600lbs	5"	12107151
900lbs	5"	12570038
1500lbs	5"	12563469
2500lbs	5"	12570039
150lbs	6"	11400252
300lbs	6"	11400271
600lbs	6"	11400281
900lbs	6"	11536801
1500lbs	6"	11536813
2500lbs	6"	12604229
150lbs	8"	11400253
300lbs	8"	11400272
600lbs	8"	11400282
900lbs	8"	11536802
1500lbs	8"	11536814
2500lbs	8"	12723285
150lbs	10"	11400254
300lbs	10"	11400273
600lbs	10"	11400283
900lbs	10"	11607785
1500lbs	10"	11536815
150lbs	12"	11400255
300lbs	12"	11400274
600lbs	12"	11400284
900lbs	12"	11536803
1500lbs	12"	11536816
150lbs	14"	11400256
300lbs	14"	11400275
600lbs	14"	11400285
900lbs	14"	11536804
1500lbs	14"	12563470
150lbs	16"	11400257
300lbs	16"	11400276
600lbs	16"	11400286
900lbs	16"	11536805
1500lbs	16"	11536817
150lbs	18"	11400258
300lbs	18"	11400277
600lbs	18"	11400287
900lbs	18"	11536806
1500lbs	18"	12563471
150lbs	20"	11400259
300lbs	20"	11400278
600lbs	20"	11400288
900lbs	20"	12563467
1500lbs	20"	11454917
150lbs	24"	11400260
300lbs	24"	11400279
600lbs	24"	11400289

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Flange pressure stage	Nominal diameter	Article
900lbs	24"	12563468

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.