



Hose EF-2 NEO, ventilation hose for hot air up to 150 °C, 2-ply neoprene glass fibre coated with embedded steel helix

Application

suction and blower hose for cold and hot air, smoke, gases, etc.

Temperature range

-35 °C to +150 °C continuous

Properties

- completely embedded steel spiral between 2 layers fiberglass cloth, neoprene impregnated and fiberglass cord
- smooth tube

Connections

free of choice or to be mounted directly on pipe

Assembly

FIXED hose clamps

Internal diameter	Outer diameter	Maximum operating pressure	Vacuum-resistance at 20 °C	Minimum bending radius	Roll length	Article
mm	mm	bar	%	mm	m	
19	33	2.8	71	31	4	10015620
25	40.2	2.8	71	37	4	10015621
32	49	2.7	65	50	4	10015622
38	55	2.7	60	60	4	10015623
44	61.4	2.7	57	70	4	10015624
51	72	2.6	52	75	4	10015625
57	75	2.5	50	88	4	10015626
63	82	2.45	47	92	4	10015627
70	92.4	2.35	45	100	4	10015628
76	104	2.3	43	116	4	10015629
83	29	2.15	40	129	4	10015630
90	12	2.1	37	140	4	10015631
95	33	2	36	150	4	10015632
102	117	1.9	35	157	4	10015633
110	16	1.7	30	165	4	10015634
114	143	1.6	27	175	4	10015635
127	18	1.4	24	197	4	10015636
130	19.2	1.3	22	200	4	10015637
140	22.6	1.2	18	220	4	10015638
152	24.4	1.1	16	237	4	10015639
180		1	12	270	4	10015640
203	38	0.85	9	330	4	10015641
254	43.4	0.7	7	399	4	10015642
305	47	0.5	5	505	4	10015643

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.