



Hose EF-1 SIL, ventilation hose for hot air up to 260 °C, 1-ply silicone glass fibre coated with exposed steel helix

Application

suction and blower hose for hot air, smoke, gases, etc.

Temperature range

-85 °C to +260 °C continuous

Properties

- exposed steel spiral with fiberglass cloth, silicone impregnated and fiberglass cord
- color red

Connections

free of choice or to be mounted directly on pipe

Assembly

FIXXED hose clamps

Internal diameter	Outer diameter	Maximum operating pressure	Vacuum-resistance at 20 °C	Minimum bending radius	Roll length	Article
mm	mm	bar	%	mm	m	
19	41	1.8			4	11224385
25	75	1.6	51	32	4	10015607
32	118	1.5	47	40	4	10015608
38	50	1.4			4	10015609
44	74	1.3			4	11224386
51	77	1.2	43	67	4	10015610
57	95	1.2			4	11224388
60	28.6	1.1	40	78	4	10014757
63	35	1.15	37	89	4	10015611
70	43	1.1	35	100	4	11028529
76	120	1.1	34	101	4	10014758
80	128	1.1	32	107	4	10014759
83	135.4	1.05	30	115	4	10015612
90	168.8	1	28	125	4	10015613
95	20	1			4	11224389
102	34	0.9	26	136	4	10014760
108	41	0.9			4	11224390
114	61.8	0.85	19	155	4	10015614
121	75	0.8			4	11020682
127	89	0.8	17	172	4	10015615
140	170	0.7	14	194	4	10015616
152	118	0.7	14	205	4	10014761
160	121.6	0.7			4	11064179
165	89	0.7			4	11224403
180	34	0.6			4	10014762
203	48	0.55	7	290	4	10015618
229	61.8	0.5			4	11113246
254	118	0.5	5	290	4	10015619

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Internal diameter	Outer diameter	Maximum operating pressure	Vacuum-resistance at 20 °C	Minimum bending radius	Roll length	Article
mm	mm	bar	%	mm	m	
305	92	0.35	5	435	4	10014763

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.