

## COMPAC Hydraulic shunting and lifting jack 1.5-2.0 tonnes



Hydraulic trolley and high jacks 1.5-20 t

- 

### Avoids overload

Integrated safety valve

- 

### Efficient working

Foot pedal for quick lift as standard.

- 

### Easy transport

Pivoting front wheels

- 



### Optional accessories

We recommend additional transport wheels for trolley jacks from 5 t and high jacks from 3 t.

- 

### Tested safety

According the principles for the test of work safety of winching, lifting and pulling devices VBG 8 and DIN 76024, Issue 1.1995.



| Lifting capacity | Min. height | Maximum lifting height | Weight | Article  |
|------------------|-------------|------------------------|--------|----------|
| kg               | mm          | mm                     | kg     |          |
| 2000             | 80          | 500                    | 36     | 23862587 |
| 3000             | 130         | 860                    | 88     | 23862590 |
| 5000             | 145         | 560                    | 71     | 23862591 |
| 6000             | 155         | 570                    | 90     | 23862592 |
| 10000            | 170         | 670                    | 136    | 23862585 |
| 15000            | 200         | 600                    | 162    | 23862586 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.