



FETRA Box carts 750kg, open or closed

For example: Box cart in angle steel construction with tubular handlebar, powder coated. Ends, 1 side, folding door and roof covered with galvanized 1 mm steel sheet. Double wing door made of angle steel with vertical locking rod and integrated cylinder lock. 1 fixed and 4 detachable wood material shelves, surface beech grain. 2 swivel and 2 fixed-wheel castors with TPE tyres (thermoplastic elastomer), hubs with precision deep groove ball bearing. Maximum comfort: Very lowstarting, rolling and swivelling esistance. Low noise operation on level floors. Tyres are non-marking [trackless]. TOTALSTOP central braking system standard on swivel castors. _x005F_x000D_Clearance between shelves 280 mm. Capacity per shelf 90 kg.

Load-bearing capacity kg	Length mm	Type of tyres	Article
750	1000	TPE rubber 200 x 50	23480226
750	1000	TPE rubber 200 x 50	23480383
750	1000	TPE rubber 200 x 50	23480269
750	1200	TPE rubber 200 x 50	23480388
750	1200	TPE rubber 200 x 50	23480270
750	1200	TPE rubber 200 x 50	23480228
750	1200	TPE rubber 200 x 50	23480385
			23479733

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.