

RHODES Sight glass device Type: 1687 Stainless steel Flange Class 150

Stainless steel sight glass with Flanged connection, pressure class 150.

Characteristics

Series: 933

Type: 1687

Norm: ASME

Housing material: Stainless steel

Material quality: ASTM A351 CF8M

Connection: Flange

Flange finish: Raised face

Face to Face norm: Manufacturer standard

Material cover: Stainless steel


Material cover gasket: PTFE

Application

- General industry.
- Corrosive media.
- For visual check of the flow in a pipeline.

Technical Information

- Suitable for mounting in horizontal and vertical pipes.
- Pay attention to flow direction because of the operation of flow indication.



Nominal inner diameter	Pressure rating	Pressure rating flange	Face to Face length	Type of flow indicator	Material glass	Minimum medium temperature [continuous]	Maximum medium temperature [continuous]	Maximum pressure difference at 20 °C	Article
			mm			°C	°C	bar	
1" [25]	Class 150	Class 150	140	Driptube	Soda lime	-10	200	20	11165036
1.1/2" [40]	Class 150	Class 150	180	Driptube	Soda lime	-10	250	25	11165037
2" [50]	Class 150	Class 150	220	Driptube	Soda lime	-10	200	20	11165038
3" [80]	Class 150	Class 150	260	Driptube	Soda lime	-10	200	20	11165039
4" [100]	Class 150	Class 150	310	Driptube	Soda lime	-10	200	20	11165040

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.