



ECON® Bourdon tube pressure gauge Type 1415A rear connection brass

Characteristics

Type: 1415A

Model: Bourdon tube pressure gauge

Blow-out included: Yes

Pressure gauge attachment: Direct

Process connection: External thread


Process connection material: Brass

Window material: Glass

Protection class: IP65

Medium temperature: -20 / 60 °C

Ambient temperature: -20 / 60 °C



Cabinet diameter	G	D	b	c	c1	c2	c3	g	g1	SW1	Weight
mm	BSPP	mm	mm	mm	mm	mm	mm	mm	mm	mm	Kg
R100	1/2"	101	55	6	3	20	19	97	96	17	0.6

Cabinet diameter mm	Measuring range	Pressure unit	Accuracy class	Cabinet filling fluid	Connection location	Size process connection	Cabinet material	Material dial	Maximum overpressure bar	Article
100	-1 / 0	bar	1.0 %	Glycerin	Back eccentric	1/2" BSPP[G]	Stainless steel 304	Aluminium	0	10059548
100	0 / 1.6	bar	1.0 %	Glycerin	Back eccentric	1/2" BSPP[G]	Stainless steel 304	Aluminium	2	10059663
100	0 / 10	bar	1.0 %	Glycerin	Back eccentric	1/2" BSPP[G]	Stainless steel 304	Aluminium	13	10059544

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.