



ECON® Bourdon tube pressure gauge Type 1401C rear connection brass front flange

Characteristics

Type: 1401C

Model: Bourdon tube pressure gauge

Blow-out included: No

Pressure gauge attachment: Front flange

Process connection: External thread

Material mounting flange: Stainless steel


Process connection material: Brass

Window material: Acrylic

Protection class: IP54

Medium temperature: 0 / 50 °C

Ambient temperature: 0 / 50 °C



Application

- Light industry.
- Pneumatics.
- Installation technique.

Technical Information

- Suitable for gases and liquids that do not affect the brass measuring system.
- Measuring ranges according to EN 837-1.
- Equipped with front flange for panel mounting.

Options

- Double scale for example in bar/psi.
- Damping screw in connection.
- Dial according to customer specification for example company logo.

Cabinet diameter	G	D	b2	c	c1	c2	d1	d2	d3	g1	s2	s3	SW	Weight
	BSPP	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg
R63	1/4"	53	32	5	2	13	62	75	85	3.6	1.5	2	14	0.13

Cabinet diameter mm	Measuring range	Pressure unit	Accuracy class	Cabinet filling fluid	Connection location	Size process connection	Cabinet material	Material dial	Maximum overpressure bar	Article
63	-1 / 0	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	0	10059726
63	-1 / 1.5	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	1.9	11110723
63	0 / 1	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	1.3	11041262
63	0 / 1.6	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	2	10059777
63	0 / 2.5	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	3	10059778
63	0 / 4	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	5	10059641
63	0 / 6	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	7.8	10059642
63	0 / 10	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	13	10059722
63	0 / 16	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	20	10059723
63	0 / 40	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	52	10059725
63	0 / 60	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	78	11037589
63	0 / 100	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	130	11037670
63	0 / 160	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	208	11016111
63	0 / 250	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	325	11070042

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.