

ECON® Bourdon tube pressure gauge Type 1414A rear connection brass




Characteristics

Type: 1414A
Model: Bourdon tube pressure gauge
Blow-out included: No
Pressure gauge attachment: Direct
Process connection: External thread
Cabinet material: Stainless steel 304
Process connection material: Brass

Characteristics [2]

Window material: Acrylic
Material dial: Aluminium
Protection class: IP65
Medium temperature: -20 / 50 °C
Ambient temperature: -20 / 50 °C



Case diameter	b	c	c1	c2	D	g	s1	SW	G
mm	mm	mm	mm	mm	mm	mm	mm	mm	[BSP]
63	32	5	2	13	67	58	6.5	17	1/4"
100	37	6	3	17	100	70	10	22	1/4"

Cabinet diameter	Measuring range	Pressure unit	Secondary scale division	Pressure unit secondary scale	Accuracy class	Cabinet filling fluid	Connection location	Size process connection	Maximum overpressure	Article
mm									bar	
63	0 / 1	bar			1.6 %	Glycerin	Back centric	1/4" BSPP[G]	1.3	11265191
63	0 / 2.5	bar			1.6 %	Glycerin	Back centric	1/4" BSPP[G]	3	11025775
63	0 / 6	bar			1.6 %	Glycerin	Back centric	1/4" BSPP[G]	7.8	11037819
63	0 / 16	bar			1.6 %	Glycerin	Back centric	1/4" BSPP[G]	20	11037821
63	0 / 25	bar			1.6 %	Glycerin	Back centric	1/4" BSPP[G]	32	11037822
63	0 / 40	bar			1.6 %	Glycerin	Back centric	1/4" BSPP[G]	52	11037823
63	0 / 160	bar			1.6 %	Glycerin	Back centric	1/4" BSPP[G]	208	11037826
63	0 / 250	bar	0 - 4000	psi	1.6 %	Glycerin	Back centric	1/4" BSPP[G]	325	10060906
63	0 / 400	bar			1.6 %	Glycerin	Back centric	1/4" BSPP[G]	520	11037827

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.