



ECON® Contact pressure gauge Type 14071 bottom connection stainless steel

Characteristics

Type: 14071

Model: Contact manometer

Blow-out included: Yes

Pressure gauge attachment: Direct

Process connection: External thread

Function at rising pressure: First contact opens, second closes

Cabinet material: Stainless steel 304

Process connection material: Stainless steel 316L

Window material: Safety glass

Material dial: Aluminium

Protection class: IP54

Medium temperature: -20 / 100 °C

Ambient temperature: -20 / 60 °C

Application

- Heavy industry.
- Refineries.
- Chemical installations.
- Food products.
- Ships.
- Recommended in: Chemical

Technical Information

- Measuring range according to EN 837-1.
- Fitted with a contact device with single or double magnetic spring contact.
- Suitable for assembly with diaphragm seals.

Cabinet diameter mm	Measuring range	Pressure unit	Accuracy class	Cabinet filling fluid	Connection location	Size process connection	Contact version	Contact type	Maximum overpressure bar	Article
100	-1 / 0	bar	1.0 %	None	Below	1/2" BSPP[G]	Single magnetic spring contact	M2	0.3	11344534
100	-1 / 0	bar	1.0 %	None	Below	1/2" BSPP[G]	Single magnetic spring contact	M 1	0.3	11116543
100	0 / 4	bar	1.0 %	None	Below	1/2" BSPP[G]	Single magnetic spring contact	M 1	5.2	11180435
100	0 / 4	bar	1.0 %	None	Below	1/2" BSPP[G]	Single magnetic spring contact	M2	5.2	11611552
100	0 / 4	bar	1.0 %	None	Below	1/2" BSPP[G]	Double magnetic spring contact	M 12	5.2	11173767
100	0 / 4	bar	1.0 %	None	Below	1/2" BSPP[G]	Double magnetic spring contact	M21	5.2	11611583
100	0 / 6	bar	1.0 %	None	Below	1/2" BSPP[G]	Double magnetic spring contact	M11	7.8	11202829
100	0 / 6	bar	1.0 %	None	Below	1/2" BSPP[G]	Double magnetic spring contact	M21	7.8	11257954
100	0 / 6	bar	1.0 %	None	Below	1/2" BSPP[G]	Double magnetic spring contact	M 12	7.8	11387259
100	0 / 6	bar	1.0 %	None	Below	1/2" BSPP[G]	Single magnetic spring contact	M2	7.8	11058240
100	0 / 6	bar	1.0 %	None	Below	1/2" BSPP[G]	Single magnetic spring contact	M 1	7.8	11117119
100	0 / 10	bar	1.0 %	None	Below	1/2" BSPP[G]	Single magnetic spring contact	M2	13	11094018
100	0 / 10	bar	1.0 %	None	Below	1/2" BSPP[G]	Double magnetic spring contact	M11	13	11611584
100	0 / 10	bar	1.0 %	None	Below	1/2" BSPP[G]	Single magnetic spring contact	M 1	13	11177260

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Cabinet diameter mm	Measuring range	Pressure unit	Accuracy class	Cabinet filling fluid	Connection location	Size process connection	Contact version	Contact type	Maximum overpressure bar	Article
100	0 / 10	bar	1.0 %	None	Below	1/2" BSPP[G]	Double magnetic spring contact	M21	13	11148951
100	0 / 16	bar	1.0 %	None	Below	1/2" BSPP[G]	Single magnetic spring contact	M2	20	11123595
100	0 / 16	bar	1.0 %	None	Below	1/2" BSPP[G]	Single magnetic spring contact	M 1	20	11611587
100	0 / 40	bar	1.0 %	None	Below	1/2" BSPP[G]	Single magnetic spring contact	M2	52	11611588
100	0 / 40	bar	1.0 %	None	Below	1/2" BSPP[G]	Single magnetic spring contact	M 1	52	11080077

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.