



Float switch fig. 8470 plastic cable



Characteristics

Type: 8470
Process connection: Cable
Contact version: Hermetic closed
Switching power: 250V AC / 10 A
Cable material: PVC



Model	Mounting	Min. specific density of liquid	Contact type	Adjustable differential gap	Float material	Cable length	Level of protection (IP value)	Article
		kg/m³				m		
Ball float switch	Horizontal and vertical	800	1 x NO en 1 x NC	Yes	PP	10	IP68	12036225
Ball float switch	Horizontal and vertical	800	1 x NO en 1 x NC	Yes	PP	20	IP68	13467626
Ball float switch	Horizontal and vertical	800	1 x NO en 1 x NC	Yes	PP	5	IP68	12036223
Ball float switch	Horizontal and vertical	800	1 x NO en 1 x NC	Yes	PP	10	IP68	12036224
Ball float switch	Horizontal and vertical	800	1 x NO en 1 x NC	Yes	PP	20	IP68	13467625
Ball float switch	Horizontal and vertical	800	1 x NO en 1 x NC	Yes	PP	5	IP68	12036222

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.