



LUDECKE MODY coupling type SSG

Characteristics

Type of component: Hose tail coupling

Material: Cast iron

Connection type: Quick Coupling

Hose fitting type: Claw coupling

Connection termination: EA Adjustable

Seal material: NBR

Elbow angle [degr.]: 0 °

Hose tail execution: Serrated

Temperature range [°C]: -40 / 95 °C

Connection termination size	Hose ID (DN)	Maximum operating pressure bar	Maximum operating pressure psi	Article
				13353251
				13353260
				13353258
				13353259
				13353261
				12394158
				12363176
Claw distance 42mm	DN10	16	232	11072204
Claw distance 42mm	DN12	16	232	11063059
Claw distance 42mm	DN12	16	232	12953561
Claw distance 42mm	DN15	16	232	11054048
Claw distance 42mm	DN19	16	232	10039525
Claw distance 42mm	DN25	16	232	11008234
Claw distance 42mm	DN25	16	232	12385769

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.