Elektrode TP / TL

Characteristics

Series: TL Type: 8701

Model: Electrode Length: 500 mm

Sensor material: Stainless steel 316L **Insulating ring material:** PTFE

type TL10B type TL308

| Туре | Material | Number of pins | Process connection | Size process connection | Electrical connection | Max. operating pressure bar | Explosion- proof | Approvals | Article |
|-------|------------------------------------|----------------|------------------------|-------------------------|--------------------------|--------------------------------------|---------------------|-----------|----------|
| TL10B | Stainless steel 316 Ti (1.4571) | 1 | External thread (BSPP) | 1/4" (8) | Plug-in connection | 5 | No | EC1935 | 10060209 |
| TL10B | Stainless steel 316 Ti (1.4571) | 1 | External thread (BSPP) | 1/4" (8) | Plug-in connection | 5 | No | EC1935 | 10060208 |
| TL30B | Stainless steel 316 Ti (1.4571) | 1 | External thread (BSPP) | 3/8" (10) | Clamping screw | 5 | No | EC1935 | 10060210 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

E-mail: valves@eriks.be

= ;0 PR_EC011206_0006_MVD_EN_19.05.2024