



Flange coupling with knurled tailpiece, type SHLF - casted steel - EN1092-1

Characteristics

Type of component: Hose tail coupling

Material: Steel

Connection type: Flange

Hose fitting type: Swivel Flange

Connection termination: EN1092 PN40

Elbow angle [degr.]: 0 °

Hose tail execution: Serrated, with safety collar

Temperature range [°C]: -40 / 100 °C

Connection termination size	Hose ID (DN)	Maximum operating pressure		Article
		bar	psi	
DN200	DN200	10	145	11164765
DN50	DN50	16	232	10037985
DN65	DN63	16	232	10069896
DN80	DN75	16	232	10037986
DN100	DN100	16	232	10037987
DN125	DN125	16	232	10037988
DN150	DN150	16	232	10037989
DN15	DN12	40	580	12493631
DN20	DN19	40	580	12493633
DN25	DN25	40	580	10037972
DN32	DN32	40	580	10069889
DN40	DN38	40	580	10037973

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.