

Grip clamp coupling in stainless steel with female thread type ECF



Characteristics

Type of component: Hose tail coupling

Material: AISI 316

Connection type: Threaded coupling

Hose fitting type: Female swivel thread

Connection termination: BSPP

Seal material: PTFE

Elbow angle [degr.]: 0 °

Hose tail execution: Smooth, with safety collar

Temperature range [°C]: -40 / 100 °C



Connection termination size	Hose ID (DN)	Maximum operating pressure		Article
		bar	psi	
2"	DN40	25	362	10070301
3/4"	DN12	25	362	10070294
1/2"	DN12	25	362	10038997
3/4"	DN19	25	362	10039000
1"	DN19	25	362	10070295
1"	DN25	25	362	10039003
1.1/2"	DN25	25	362	10070452
1.1/4"	DN25	25	362	10070296
1.1/2"	DN32	25	362	10070298
1.1/4"	DN32	25	362	10070297
1.1/2"	DN38	25	362	10039010
2"	DN38	25	362	10070299
2"	DN50	25	362	10039015
2.1/2"	DN50	25	362	10070453
2.1/2"	DN63	25	362	10070302
3"	DN75	25	362	10039023
4"	DN100	25	362	10070333

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.