

GATES Hydraulic hose MegaSys® EFG5K-MTF (R13) MegaTuff

Characteristics

Series: MegaSys® MegaTuff™

Type: EFG5K-MTF

Material of inner wall: NBR

Material of outer wall: CR

Quality cover: Gates Megatuff

Temperature range [°C]: -40 / 121 °C

EN standard: EN 856-R13

SAE standard: SAE 100 R13

ISO standard: ISO 3862 R13

Application

- Extremely high pressure and high impulse hydraulic applications.

Technical Information

Temperature range:

- 40°C to +121°C

Construction

Tube:

- NBR (Nitrile) based.

Reinforcement:

- Four (six for -20 to -32) alternating layers of spiralled, high tensile steel wire.

Cover:

- CR (Chloroprene) based.
- MSHA approved.

Execution

- Up to 40% of EN 856 4SP/4SH bend radius at rated working pressure.
- Extremely flexible.
- Superior flex impulse performance: tested to 1,000,000 impulse cycles at 50% of EN 856 R13 and SAE 100R13 bend radii (except -32).
- EFG5K hose is compatible with biodegradable hydraulic fluids like synthetic esters, polyglycols and vegetable oils as well as petroleum-based fluids.
- Gates special MegaTuff™ cover offers 300 times the abrasion resistance of the standard EFG5K cover as per ISO 6945, superior ozone and weathering resistance.

Approval

Standards:

- Exceeds ISO 3862 R13. EN 856 R13. SAE 100 R13.
- Meets or exceeds performance requirements of EN 856 4SP [-10 to -32] and EN 856 4SH [-20 to -32].

Type approval:

- DNV

Options

Recommended couplings:

- 6 to -20: GlobalSpiral
- 24, -32: GlobalSpiral Maximum

Code	Hose ID (DN)	Hose ID	Outer diameter	Maximum operating pressure	Minimum burst pressure	Minimum bending radius	Outside wall colour	Weight	Article
		in	mm	bar	bar	mm		kg/m	
6EFG5K-MTF	DN10	3/8"	20.2	350	1400	65	Black	0.71	11373911
8EFG5K-MTF	DN12	1/2"	24	350	1400	90	Black	0.89	11373912
10EFG5K-MTF	DN16	5/8"	27.6	350	1400	100	Black	1.15	1023371
12EFG5K-MTF	DN19	3/4"	31.4	350	1400	120	Black	1.44	949078
16EFG5K-MTF	DN25	1"	38.7	350	1400	150	Black	2.23	1028094
20EFG5K-MTF	DN31	1.1/4"	50	350	1400	210	Black	3.99	1021389
24EFG5K-MTF	DN38	1.1/2"	57.4	350	1400	250	Black	4.82	973297
32EFG5K-MTF	DN51	2"	71.1	350	1400	635	Black	7.19	1021051

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.