



Rubber hose Eriduct, NR light vacuum cleaner hose, antistatic

Application

- flexible suction hose for pneumatic conveying of dust, chips, sawdust, paper, fibres, fumes, etc.

Technical Information

Temperature range

- 20 °C to +60 °C

Construction

Tube

- black NR rubber
- smooth
- antistatic $R < 10^6 \Omega$

Reinforcement

- spiral-plied textile fabrics and steel spiral, vacuum resistant

Cover

- brown/beige gummed synthetic cord
- corrugated

Execution

Branding

- white marking with text: "ERIDUCT"

Connections

- free of choice or to be mounted directly on pipe

Assembly

- FIXXED hose clamps or Band-it

Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure	Vacuum-resistance at 20 °C	Minimum bending radius	Roll length	Article
mm	mm	mm	bar	%	mm	m	
38	3.5	45	2	60	75	6	10015106
50	3.5	57	2	60	115	6	10015107
63	3.5	70	2	60	150	6	10015108
76	4	84	2	60	165	6	10015109
90	4	98	2	60	205	6	10015111
102	4	110	2	60	230	6	10015112
115	4	123	2	60	240	6	10015113
127	4	135	2	60	300	6	10015114
150	4	158	2	60	320	6	10015115

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.