



Rubber hose Goldschlange, EPDM water discharge hose up to 30 bar

Characteristics

Series: Goldschlange

Application

- universal industrial hose
- robust and dependable
- meets all requirements for the building industry, agriculture and many other applications
- suitable for all thinkable working conditions
- non-buckling, shock-proof, can be overrun

Technical Information

Temperature range

- -30 °C to +100 °C
- steam cleaning up to 130 °C (max. 30 minutes, without pressure)

Burst pressure

- 3 x working pressure
- safety factor 3:1

Construction

Tube

- black EPDM rubber

Reinforcement

- spiral-ply polyamide fabrics

Cover

- CR rubber, yellow wavy line on black cover
- extremely wear resistant and durable
- also resistant to oil, fat and petrol
- ozone and weather resistant

Execution

Connections

- free of choice

Assembly

- FIXXED hose clamps or from DN25 safety clamps

Options

Additional information

- this hose is ADI-free (Animal Derived Ingredient Free)

Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure	Minimum burst pressure	Minimum bending radius	Roll length	Weight	Article
mm	mm	mm	bar	bar	mm	m	kg/m	
10	3.6	17.2	30	90	45	40	0.16	10014961
13	3.9	20.8	30	90	50	40	0.23	10014962
16	3.6	23.2	25	75	70	40	0.26	10014963
19	4.4	27.8	25	75	80	40	0.39	10014964
22	4.5	31	20	60	100	40		10014965
32	5.5	43	12	36	175	40	0.76	10014967
38	6.5	51	12	36	250	40	1.05	10014968
50	7.5	65	10	30	300	40	1.58	10014969

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.