



Rubber hose Orange Star, SBR propane and butane gas hose; according to ISO 3821 (EN 559)

Hose for propane and butane installations.

Tube: black SBR rubber, gas tight

Reinforcement: textile fabrics

Cover: orange CR/NR rubber

Black marking with text: "ORANGE STAR - ISO 3821 - PN 2MPa (20 bar) DN... -30 °C - year"

Working pressure: 20 bar

Temperature range: -30 °C to +70 °C

Connections: free of choice

Assembly: FIXXED ear clamps or ferrules according ISO 1256:2006



Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure	Minimum burst pressure	Minimum bending radius	Roll length	Article
mm	mm	mm	bar	bar	mm	m	
8	3.5	15	20	60	80	50	10015195
9	3.5	16	20	60	45	50	11250127
10	3.5	17	20	60	50	50	11163023
63	3.5		20	60	40	50	11250126
							13585677

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.