

Rubber hose SM1 Sandblast, SBR/NR/BR premium shot blast hose 12 bar 36 mm³

Application

- premium shot blast hose, specially designed for a long life in heavy applications
- special suitable for transport of quarts, glass, corundum, sand, etc.

Technical Information

- Temperature range
- -35 °C to +80 °C
- Burst pressure
- minimum 42 bar
- safety factor 3,5:1

Construction

Tube

- black SBR/NR/BR rubber
- electrically conductive
- extremely wear resistant [+/- 36 mm³ in accordance with ISO 4649:2021]

Reinforcement

woven textile fabrics

Cover

- black SBR rubber
- wear resistant, antistatic
- durable
- cloth impression

Execution

Branding

- yellow marking with text: "SM1[®] Sandstrahl-Shotblast Strahlmeister[®] PN 12 bar"
- Connectionsshot blast couplings
- Assembly
- Assembly
- by self-tapping screw

Options

Complete assembly

• ERIKS can assemble the SM1[®] Sandblast with your required couplings.

Options

- hydrostatic test report
- excellent laser engraving on marking ferrule

Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure	Minimum burst pressure	Minimum bending radius	Roll length	Weight	Article
mm	mm	mm	bar	bar	mm	m	kg/m	
13	7	27	12	36	130	40	0.5	12691264

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1

