



ECON® Ball valve Type: 7544 Stainless steel Internal thread (NPT) 1000 PSI WOG



Characteristics

Type: 7544
Norm: ASME
Construction type: 2-way
Housing construction: 3-part
Housing material: Stainless steel
Material quality: 1.4408
Connection: Internal thread (NPT)
Top flange standard: ISO 5211 Direct Mount
Bore: Full bore
Material ball: 1.4408
Seat material: PTFE
Spindle material: 1.4401
Primary spindle seal material: PTFE
Secondary spindle seal material: FPM (FKM)
Tertiary spindle seal material: PTFE
Body seal: PTFE
Minimum medium temperature (continuous): -29 °C
Maximum medium temperature (continuous): 205 °C

Application

- Compressed air, central heating systems, water, fuel and slightly corrosive systems up to a maximum of 68 bar.
- Recommended in: Food & Beverages

Technical Information

- Connection according to ASME B1.20.1 NPT.
- Floating ball.
- Pressure class 1000 PSI WOG
- In sizes 0.25-4 inches.
- With "direct mount" top-flange in accordance with ISO-5211.
- Cavity relief bore in the ball.
- Double self-adjusting gland packing in accordance with TA Luft regulations.
- Equipped with lockable lever.

Construction


- Three-piece housing construction.
- Design in accordance with MSS SP-110.
- Full bore.
- Equipped with anti-static design between ball, spindle and housing.

Approval

- TA Luft certified in accordance with VDI 2440, section 3.3.1.3.
- Declaration of conformity according to EC 1935/2004.

Options

- Equipped with worm gearbox and pneumatic, electric or hydraulic actuators.
- Position feedback for manual or automated valves.
- Steel housing, type 7524
- Ball seals in TFM4215
- Stainless steel extended spindle type 8007 for insulation.
- Connection in BSP according to ISO 228-1, type 7444
- Connection in projection welding acc. to B16.11 or butt-welding acc. to B16.25, Schedule 40, type 7644



Size table:

DN	d mm	L mm	H mm	M mm	Weight kg
1/4" [8]	10.6	75	72	147	0.6
3/8" [10]	12.7	75	72	147	0.6
1/2" [15]	15	75	72	147	0.7
3/4" [20]	20	80	79	147	0.9
1" [25]	25	90	89	177	1.4
1.1/4" [32]	32	110	93	177	2
1.1/2" [40]	38	120	103	197	3
2" [50]	50	140	110	197	4.3
2.1/2" [65]	63.5	185.5	150	267	8.2
3" [80]	76	205	159	267	11.2
4" [100]	100	240	212	400	22.1

Pressure and temperature range

Size	Temperature range	-29	38	100	150	200	[°C]
1/4" - 2"	-29°C/+200°C	68	68	44	22	1	[bar]
2.1/2" - 4"	-29°C/+200°C	50	50	32	16	1	[bar]

Pressure class 1000 PSI WOG

Nominal inner diameter	Standard thread connection	Pressure rating	Face to Face norm	Manual operation	Mounting flange	Mounting flange 2	With locking device	Actuator material	Maximum operating pressure bar	Article
1/4" [8]	ASME B1.20.1	1000 PSI WOG	Manufacturer standard	Handle	F03	F04	Yes	1.4301	63	11814507
3/8" [10]	ASME B1.20.1	1000 PSI WOG	Manufacturer standard	Handle	F03	F04	Yes	1.4301	63	11814508
1/2" [15]	ASME B1.20.1	1000 PSI WOG	Manufacturer standard	Handle	F03	F04	Yes	1.4301	63	11814509
3/4" [20]	ASME B1.20.1	1000 PSI WOG	Manufacturer standard	Handle	F03	F05	Yes	1.4301	63	11814510
1" [25]	ASME B1.20.1	1000 PSI WOG	Manufacturer standard	Handle	F04	F05	Yes	1.4301	63	11814511
1.1/4" [32]	ASME B1.20.1	1000 PSI WOG	Manufacturer standard	Handle	F04	F07	Yes	1.4301	63	11814512
1.1/2" [40]	ASME B1.20.1	1000 PSI WOG	Manufacturer standard	Handle	F05	F07	Yes	1.4301	63	11814513
2" [50]	ASME B1.20.1	1000 PSI WOG	Manufacturer standard	Handle	F05	F07	Yes	1.4301	63	11814514
2.1/2" [65]	ASME B1.20.1	1000 PSI WOG	Manufacturer standard	Handle	F07	F10	Yes	1.4301	51	11814515
3" [80]	ASME B1.20.1	1000 PSI WOG	Manufacturer standard	Handle	F07	F10	Yes	1.4301	51	11814516
4" [100]	ASME B1.20.1	1000 PSI WOG	Manufacturer standard	T-wrench	F10		No	Steel, galvanized	51	11814464

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.