



ECON® Ball valve Type: 7644 Stainless steel Butt weld B16.25 S40 1000 PSI WOG



Characteristics

Type: 7644
Norm: ASME
Construction type: 2-way
Housing construction: 3-part
Housing material: Stainless steel
Material quality: 1.4408
Connection: Butt weld
Standard welding connection: B16.25 S40
Face to Face norm: Manufacturer standard
Top flange standard: ISO 5211 Direct Mount
Bore: Full bore
Material ball: 1.4408
Seat material: PTFE
Spindle material: 1.4401
Primary spindle seal material: PTFE
Secondary spindle seal material: FPM (FKM)
Tertiary spindle seal material: PTFE
Body seal: PTFE
Minimum medium temperature (continuous): -29 °C
Maximum medium temperature (continuous): 205 °C

Application

- Compressed air, central heating systems, water, fuel and slightly corrosive systems up to a maximum of 68 bar.
- Recommended in: Food & Beverages

Technical Information

- Connection according to ASME B16.25, Schedule 40 (butt-welding)
- Floating ball.
- Pressure class 1000 PSI WOG
- In sizes 0.25-4 inches.
- With "direct mount" top-flange in accordance with ISO-5211.
- Cavity relief bore in the ball.
- Double self-adjusting gland packing in accordance with TA Luft regulations.
- Equipped with lockable lever, 4 inches with T-wrench.

Construction


- Three-piece housing construction.
- Design in accordance with MSS SP-110.
- Full bore.
- Equipped with anti-static design between ball, spindle and housing.

Approval

- TA Luft certified in accordance with VDI 2440, section 3.3.1.3.
- Declaration of conformity according to EC 1935/2004.

Options

- Equipped with worm gearbox and pneumatic, electric or hydraulic actuators.
- Position feedback for manual or automated valves.
- Steel housing, type 7624
- Ball seals in TFM4215
- Stainless steel extended spindle type 8007 for insulation.
- Connection according to ASME B16.11.
- Connection in NPT according to ASME B1.20.1, type 7544
- Connection in BSP according to ISO 228-1, type 7444
- Connection in butt weld according to ISO 1127-1, type 7621
- With rotating butt-weld ends (quick-weld design) according to ISO 1127-1, type 7641, ASME B16.25, type 7654, EN 10357-A or EN 10357-D, type 7611, and ASME B16.25 for cold applications down to -40°C, type 7645



Size table:

DN	d mm	L mm	H mm	M mm	C mm	Weight kg
1/4" [8]	10.6	70	72	147	17.8	0.7
3/8" [10]	12.7	70	72	147	17.8	0.7
1/2" [15]	15	75	72	147	22	0.7
3/4" [20]	20	90	79	147	28.2	0.9
1" [25]	25	100	89	177	34	1.4
1.1/4" [32]	32	110	93	177	43.5	2.1
1.1/2" [40]	38	125	103	197	50.4	3
2" [50]	50	150	110	197	61.5	4.3
2.1/2" [65]	63.5	190	149	267	77.3	8.3
3" [80]	76	220	159	267	93	11.9
4" [100]	100	270	212	400	116	22.7

Pressure and temperature range

Size	Temperature range	-29	38	100	150	200	[°C]
1/4" - 2"	-29°C/+200°C	68	68	44	22	1	[bar]
2.1/2" - 4"	-29°C/+200°C	50	50	32	16	1	[bar]

Pressure class 1000 PSI WOG

Nominal inner diameter	External tube diameter of connection	Wall thickness, connection	Pressure rating	Manual operation	Mounting flange	Mounting flange 2	With locking device	Actuator material	Maximum operating pressure	Article
mm	mm	mm							bar	
1/4" [8]	17.8	4.25	1000 PSI WOG	Handle	F03	F04	Yes	1.4301	63	11814602
3/8" [10]	17.8	2.65	1000 PSI WOG	Handle	F03	F04	Yes	1.4301	63	11814603
1/2" [15]	22	3.1	1000 PSI WOG	Handle	F03	F04	Yes	1.4301	63	11814604
3/4" [20]	28.2	3.6	1000 PSI WOG	Handle	F03	F05	Yes	1.4301	63	11814605
1" [25]	34	3.65	1000 PSI WOG	Handle	F04	F05	Yes	1.4301	63	11814606
1.1/4" [32]	43.5	4.2	1000 PSI WOG	Handle	F04	F07	Yes	1.4301	63	11814607
1.1/2" [40]	50.4	4.75	1000 PSI WOG	Handle	F05	F07	Yes	1.4301	63	11814608
2" [50]	61.5	4.5	1000 PSI WOG	Handle	F05	F07	Yes	1.4301	63	11814609
2.1/2" [65]	77.3	7.3	1000 PSI WOG	Handle	F07	F10	Yes	1.4301	51	11814610
3" [80]	93	7.5	1000 PSI WOG	Handle	F07	F10	Yes	1.4301	51	11814611
4" [100]	116	6.85	1000 PSI WOG	T-wrench	F10		No	Steel, galvanized	51	11814612

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.