



ECON® Ball valve Type: 7646 Stainless steel Butt weld B16.25 S40 1000 PSI WOG



Characteristics

Type: 7646
Norm: ASME
Construction type: 2-way
Housing construction: 3-part
Housing material: Stainless steel
Material quality: 1.4408
Connection: Butt weld
Standard welding connection: B16.25 S40
Seat material: PTFE
Spindle material: 1.4401
Primary spindle seal material: PTFE
Tertiary spindle seal material: PTFE
Body seal: PTFE
Actuator material: 1.4301
Minimum medium temperature (continuous): -29 °C
Maximum medium temperature (continuous): 205 °C

Application

- Light industrial applications up to 68 bar.
- Recommended in: Food & Beverages

Technical Information

- Connection according to ASME B16.11 (projection welding) or ASME B16.25, Schedule 40 (butt-welding)
- Floating ball.
- Pressure class 1000 PSI WOG
- In sizes 0.25-3 inches
- Cavity relief bore in the ball.
- Equipped with lockable lever.

Construction


- Three-piece housing construction.
- Design in accordance with MSS SP-110.
- Full bore.
- Equipped with anti-static design between ball, spindle and housing.

Options

- Connection in NPT according to ASME B1.20.1, type 7546
- Connection in BSP according to ISO 228-1, type 7446
- With "direct mount" top-flange in accordance with ISO 5211, type 7644

Size table:

DN	d	L	H	M	C	Weight
	mm	mm	mm	mm	mm	kg
1/4" [8]	10.6	65.2	58	100	18	0.5
3/8" [10]	12.7	65.2	58	100	18	0.5
1/2" [15]	15	75	58	100	22	0.5
3/4" [20]	20	90	63	129	28	0.7
1" [25]	25	100	76	156	34	1.4
1.1/4" [32]	32	110	81	156	43	1.8
1.1/2" [40]	38	125	94	184	50	2.5
2" [50]	50	150	105	184	61	3.7
2.1/2" [65]	63.5	190	131	252	76	7
3" [80]	76	220	139	252	92	10.5



Pressure and temperature range							
Size	Temperature range	-29	38	100	150	200	[°C]
1/4" - 2"	-29°C/+200°C	68	68	44	22	1	[bar]
2.1/2" - 3"	-29°C/+200°C	50	50	32	16	1	[bar]
Pressure class 1000 PSI WOG							

Nominal inner diameter	External tube diameter of connection	Wall thickness, connection	Pressure rating	Face to Face norm	Manual operation	Bore	With locking device	Material ball	Maximum operating pressure bar	Article
mm	mm	mm								
1/4" [8]	18	4.35	1000 PSI WOG	Manufacturer standard	Handle	Full bore	Yes	1.4408	63	11814624
3/8" [10]	18	2.75	1000 PSI WOG	Manufacturer standard	Handle	Full bore	Yes	1.4408	63	11814625
1/2" [15]	22	3.1	1000 PSI WOG	Manufacturer standard	Handle	Full bore	Yes	1.4408	63	11814626
3/4" [20]	28	3.55	1000 PSI WOG	Manufacturer standard	Handle	Full bore	Yes	1.4408	63	11814627
1" [25]	34	3.65	1000 PSI WOG	Manufacturer standard	Handle	Full bore	Yes	1.4408	63	11814628
1.1/4" [32]	43	3.95	1000 PSI WOG	Manufacturer standard	Handle	Full bore	Yes	1.4408	63	11814629
1.1/2" [40]	50	4.55	1000 PSI WOG	Manufacturer standard	Handle	Full bore	Yes	1.4408	63	11814630
2" [50]	61	4.25	1000 PSI WOG	Manufacturer standard	Handle	Full bore	Yes	1.4408	63	11814631
2.1/2" [65]	76	6.65	1000 PSI WOG	Manufacturer standard	Handle	Full bore	Yes	1.4408	51	11814632
3" [80]	92	7	1000 PSI WOG	Manufacturer standard	Handle	Full bore	Yes	1.4408	51	11814633

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.