

MECAFRANCE Ball valve Type: 3462 Steel Butt weld EN ISO 1127-1 PN50 to PN100




Characteristics

Type: 3462
Norm: EN (DIN)
Construction type: 2-way
Housing construction: 3-part
Housing material: Steel
Material quality: 1.0619
Connection: Butt weld
Standard welding connection: EN ISO 1127-1
Top flange standard: ISO 5211

Characteristics (2)

Spindle material: 1.4404
Primary spindle seal material: RPTFE
Tertiary spindle seal material: RPTFE
Body seal: PTFE
Actuator material: Steel



Nominal inner diameter	External tube diameter of connection mm	Wall thickness, connection mm	Pressure rating	Face to Face norm	Manual operation	Mounting flange	Bore	Material ball	Seat material	Article
1/2" [15]	21.3	2	PN100	Manufacturer standard	Handle	F03	Full bore	1.4408	PTFE	12571012
3/4" [20]	26.9	2	PN100	Manufacturer standard	Handle	F04	Full bore	1.4408	PTFE	12571013
1" [25]	33.7	2.3	PN80	Manufacturer standard	Handle	F04	Full bore	1.4408	PTFE	11378418
1.1/4" [32]	42.4	2.6	PN63	Manufacturer standard	Handle	F05	Full bore	1.4408	PTFE	12571014
1.1/2" [40]	48.3	2.6	PN63	Manufacturer standard	Handle	F05	Full bore	1.4408	PTFE	12571015
2" [50]	60.3	2.6	PN50	Manufacturer standard	Handle	F07	Full bore	1.4408	PTFE	12571016

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.