



BLICKLE Castor wheel, series B-POEV

Pressed steel fixed castor, medium duty brackets, with top plate fitting, Heavy duty wheel with elastic solid rubber tyres 'Blickle EasyRoll', with nylon wheel centreBracket: Made of pressed steel. Bolted wheel axle. Zinc-plated, blue-passivated, Cr6-free. Wheels: Tyre & running tread: Made of high-quality elastic solid rubber in smooth rolling quality "Blickle EasyRoll". Color: black, Shore: 65° Shore A High chemical resistance to many aggressive substances, except oils. Operating temperature: -25° C to +80° C, temporarily up to +100° C. At ambient temperatures above +35° C the load capacity is reduced. Maintenance-free under standard conditions.

Characteristics

Series: B-POEV

Type: B-POEV 160R

Wheel model	Tread material	Diameter mm	Width mm	Bearing weight kg	Bearing	Temperature range °C	Article
Rigid caster	Solid rubber	80	32	140	Needle roller bearing	-25 / 80	11588581
Rigid caster	Solid rubber	100	38	150	Ball bearing	-25 / 80	12103541
Rigid caster	Solid rubber	100	38	200	Needle roller bearing	-25 / 80	12535072
Rigid caster	Solid rubber	100	38	200	Ball bearing	-25 / 80	12535067
Rigid caster	Solid rubber	125	40	150	Ball bearing	-25 / 80	11393729
Rigid caster	Solid rubber	125	40	150	Needle roller bearing	-25 / 80	10069347
Rigid caster	Solid rubber	125	40	200	Needle roller bearing	-25 / 80	12370354
Rigid caster	Solid rubber	125	40	200	Ball bearing	-25 / 80	12535087
Rigid caster	Solid rubber	160	40	300	Ball bearing	-25 / 80	12535142
Rigid caster	Solid rubber	160	50	300	Ball bearing	-25 / 80	11070019
Rigid caster	Solid rubber	160	50	300	Needle roller bearing	-25 / 80	10069348
Rigid caster	Solid rubber	160	50	400	Ball bearing	-25 / 80	12535116
Rigid caster	Solid rubber	200	50	300	Ball bearing	-25 / 80	10069349
Rigid caster	Solid rubber	200	50	400	Ball bearing	-25 / 80	11654879

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.