



BLICKLE Castor wheel, series BO-GTH

Welded steel heavy duty fixed castor, Heavy duty wheel with Blickle Extrathane® polyurethane tread, with cast iron wheel centreBracket: Particularly rugged welded steel construction. Bolted wheel axle. Lacquered, red. Wheels: Tyre & running tread: Made of high-quality polyurethane-elastomer Blickle Extrathane®. Color: light brown, Shore: 92° Shore AHigh chemical resistance to many aggressive substances. Operating temperature: -25° C to +70° C, temporarily up to +90° C. At ambient temperatures above +40° C the load capacity is reduced. The indicated load capacity refers to applications without obstacles. Maintenance-free under standard conditions.

Characteristics

Series: BO-GTH

Type: BO-GTH 127K

Wheel model	Tread material	Diameter	Width	Bearing weight	Bearing	Temperature range	Article
		mm	mm	kg		°C	
Rigid caster	PUR (Polyurethane)	200	50	1000	Ball bearing	-25 / 70	12443376
Rigid caster	PUR (Polyurethane)	250	50	1200	Ball bearing	-25 / 70	12534924

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.